

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	CLOSURE		Dogleg Severity Deg/100
							Distance FT	Direction Deg	
12608.00	90.80	90.50	11381.55	-34.36	1357.92	1357.32	1358.36	91.45	.00
12640.00	90.70	90.30	11381.13	-34.58	1389.92	1389.31	1390.35	91.43	.70
12672.00	90.10	90.20	11380.91	-34.72	1421.92	1421.31	1422.34	91.40	1.90
12703.00	90.40	90.20	11380.78	-34.83	1452.92	1452.30	1453.33	91.37	.97
12735.00	90.30	89.80	11380.58	-34.83	1484.92	1484.30	1485.32	91.34	1.29
12798.00	91.10	89.80	11379.81	-34.61	1547.91	1547.29	1548.30	91.28	1.27
12818.00	91.20	89.70	11379.41	-34.52	1567.91	1567.28	1568.29	91.26	.71
12830.00	91.40	89.60	11379.14	-34.45	1579.90	1579.28	1580.28	91.25	1.86
12862.00	88.80	88.90	11379.08	-34.03	1611.90	1611.28	1612.26	91.21	8.41
12894.00	88.90	88.20	11379.72	-33.22	1643.88	1643.27	1644.22	91.16	2.21
12926.00	89.70	88.40	11380.11	-32.27	1675.86	1675.26	1676.17	91.10	2.58
12941.00	89.60	88.30	11380.21	-31.84	1690.86	1690.26	1691.16	91.08	.94
12957.00	89.80	88.10	11380.29	-31.34	1706.85	1706.26	1707.14	91.05	1.77
12989.00	87.50	88.20	11381.04	-30.30	1738.82	1738.24	1739.08	91.00	7.19
13020.00	87.40	87.70	11382.42	-29.19	1769.77	1769.20	1770.01	90.95	1.64
13052.00	87.40	87.50	11383.87	-27.86	1801.71	1801.16	1801.92	90.89	.62
13083.00	87.90	87.20	11385.15	-26.42	1832.65	1832.11	1832.84	90.83	1.88
13115.00	87.20	87.20	11386.51	-24.86	1864.58	1864.06	1864.75	90.76	2.19
13146.00	87.10	86.90	11388.05	-23.27	1895.50	1895.00	1895.65	90.70	1.02
13173.00	87.10	86.90	11389.42	-21.81	1922.43	1921.95	1922.55	90.65	.00
--Projection to Bit--									
13220.00	87.10	86.90	11391.80	-19.27	1969.30	1968.85	1969.39	90.56	.00