

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-34792
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. B-10629
7. Lease Name or Unit Agreement Name Big Flat ASN State
8. Well No. 2
9. Pool name or Wildcat Shoebar Strawn, Northwest

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	
2. Name of Operator YATES PETROLEUM CORPORATION	
3. Address of Operator 105 South 4th St., Artesia, NM 88210	
4. Well Location Unit Letter <u>P</u> : <u>330</u> Feet From The <u>South</u> Line and <u>330</u> Feet From The <u>East</u> Line Section <u>10</u> Township <u>16S</u> Range <u>35E</u> NMPM Lea County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3990' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Intermediate casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4695'. Reached TD at 11:15 AM 1-23-2000. Ran 105 joints of 9-5/8" 36# & 40# N-80 & J-55 (4701.28') of casing set at 4695'. 1-Texas Pattern notched guide shoe set at 4695'. Float collar set at 4651'. Cemented with 1400 sacks of Poz C (65-35-6), 6% gel, 5#/sack salt and 1/4#/sack celloflake (yield 2.03, weight 12.5). Tailed in with 200 sacks of Class C with 1% CaCl2 (yield 1.34, weight 14.8). PD 5:00 AM 1-24-2000. Bumped plug to 2000 psi, OK. Circulated 10 sacks. WOC. Nippled up and tested to 1000# for 15 minutes, OK. Drilled out at 7:00 PM 1-25-2000. WOC 38 hours. Reduced hole to 8-3/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE Feb. 24, 2000

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: