

State of New Mexico
Energy, Minerals and Natural Resources Department

DISTRICT I
P.O. Box 1980, Hobbs NM 88240

DISTRICT II
P.O. Drawer DD, Artesia NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL APN NO.
30-025-34908

5. Indicate Type of Lease
State ☐ FEE ☒

7. Lease Name or Unit Agreement Name

BIG BEAR ATN

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL ☐ GAS ☐
WELL ☐ WELL ☒ OTHER ☐

2. Name of Operator
Yates Petroleum Corporation

8. Well No.
1

3. Address of Operator
105 South 4th., Artesia, NM 88210

9. Pool Name or Wildcat
Townsend Perma Upper Penn

4. Well Location
Unit Letter SI : 1980 Feet From The South Line and 1120 Feet From The East Line
Section 29 Township T15S Rang R35E NMPM Lea COUNTY

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
4001' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER Re-entry ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8-21-01- miru PULLING UNIT. Tag PBTD @ 12,054'. SI.

8-23-01- Rig up wireline. TIH w/4" casing guns. Perforated Atoka Sand 11,796-820' 6 JSPF = 84 .42" holes.
Rig down wireline. Spot 5 bbls 7-1/2% Morrow Acid.

8-24-01- Rig up acid equipment. Acidized Atoka Sand w/ 1000 gal 7-1/2% Morrow Acid w/1500 SCF N2/bbl.

11-6-01- Released packer. ND tree & NU BOP. TOH & RU wireline. TIH; TOH. TIH w/5-1/2" C, set @ 11,750'.

Cap w/ 35' cement. TIH w/ 4" casing gun. Correlated & perforated Strawn Lime 11,536-653' (2JSPF) w/ 28 .42" holes. SI.

11-8-01- Acidized w/ 2000 gals 15% IC HCL w/ 15 bbls acid in formation.

11-13-01- TOH w/ packer. Rig up wireline. TIH w/ 5-1/2" CIBP, set @ 11,495'. Cap w/ 35' cement. TIH w/ 4" casing gu

11-14-01- TIH w/ packer & RBP @ 11,223'. Acidized w/ 2000 gal 15% IC HCL w/ 10 bbls acid in formation.

11-19-01- Released packer & RBP. TOH. TIH w/ production string. ND BOP. Rig down.

I hereby certify that the information above is a true and complete to the best of my knowledge and belief.

SIGNATURE Donna Clack

TITLE Operations Technician

DATE 1/25/02

TYPE OR PRINT NAME Donna Clack

TELEPHONE NO 505-748-1471

(This space for State Use)

APPROVED BY _____ TITLE _____

CONDITIONS OF APPROVAL, IF ANY:

DATE

ORIGINAL SIGNED BY
PAUL F. KAUTZ
PETROLEUM ENGINEER

FEB 26 2002