

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO.

30-025-34959

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

V-5086

7. Lease Name or Unit Agreement Name:

BLTN AUy State

7. Well No.

#1

8. Pool name or Wildcat

Townsend Mississippian

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter **A** : **660** feet from the **North** line and **660** feet from the **East** line

Section **33** Township **16S** Range **35E** NMPM **Lea** County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3983' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Set production casing, Cement ☒

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

5/29/00 - Ran 314 jts. (13,040.03') 5-1/2" 17# S/P110 casing set at 13,025'. Float shoe set at 13,025'. Bottom marker set at 11,922.48'. Top marker set at 10,689.30'. Cemented with 750 sxs Super H Premium with .5% Halad 344, .1% HR-7, .4% CFR-3, 5 pps Gilsonite and 1 pps salt (yld 1.67, wt 13.0). PD 9:00 AM. Bumped plug to 2750 psi for 1 min. Held OK.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Susan Herpin

TITLE

Engineering Technician

DATE

September 4, 2001

Type or print name

Susan Herpin

Telephone No.

505-748-1471

(This space for State use)

APPROVED BY

TITLE

DATE

Conditions of approval, if any: