Submit 2 Conjec To Appropriate Dictaint				
Submit 3 Copies To Appropriate District Office	State of New Mexico		Form C-103 Revised March 25, 1999	
<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240	Energy. Minerals and Natural Resources		WELL API NO.	
District II	OIL CONSERVATION DIVISION		30-025-34959	
811 South First, Artesia, NM 88210 <u>District III</u>	1220 South St. Francis Dr.		5. Indicate Type of Lease	
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505		STATE X FEE 6. State Oil & Gas Lease No.	
1220 S. St. Francis Dr., Santa Fe, NM 87505	, ,		V-5086	
SUNDRY NOTICES AND REPORTS ON WELLS			7. Lease Name or Unit Agreement Name:	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH				
PROPOSALS.)	ATION FOR PERMIT (FORM (-101))	OK SUCH	BLTN AUY Stat	e
1. Type of Well:				
Oil Well Gas Well X Other 2. Name of Operator			7. Well No.	
Yates Petroleum Corporation			#1	
3. Address of Operator			π 8. Pool name or Wildcat	
105 S. 4 th Street Artesia, NM 88210			Townsend Mississippian	
4. Well Location				
Unit Letter A: 660	0 feet from the North li	ne and 660	feet from the Eas	t line
Section 33	Township 16S Rang		NMPM Lea	County
	10. Elevation (Show whether D		с.)	and the second
3983' GR 11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data				
NOTICE OF IN			SEQUENT REI	
	PLUG AND ABANDON	REMEDIAL WOR	K	
	CHANGE PLANS	COMMENCE DR	ILLING OPNS. X	
PULL OR ALTER CASING		CASING TEST A CEMENT JOB	ND	
OTHER:		OTHER:		
	parations (Claurly state all parting		nortinant datas inclu	
Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or				
recompilation.				
4/13/00 – Resumed driiling at 4:30 PM. TD 14-3/4" hole at 408' at 10:00 PM.				
Ran 10 jts. (411.70') 11-3/4" 42# H-40 8R ST&C csg set at 408'. Texas Pattern notched guide shoe set at 408'.				
Insert float set at 363.52'. Cemented with 350 sxs Premium Plus + 2% CaCl2 (yld 1.34, wt 14.8). 4/14/00 – PD at 2:45 AM. Bumped plug to 330 psi, held OK. Circ 25 sxs. Notified Sylvia Dickey with Hobbs OCD				
of operations. Drilled out at 9:00 PM. WOC/18 hrs, 15 mins. Reduced hole to 11" and resumed drilling.				
4/24/00 - Reached TD of 11" hole at 8:00 AM. Ran 113 jts. 8-5/8" 32# J-55 ST&C csg set at 4975'. Float collar set				
at 4936'. Cemented with 1650 sxs Interfill "C" + .25 pps flocele (yld 2.46, wt 11.9) Tailed in with 250 sxs Premium				
Plus + 2% CaCl2 (yld 1.32, wt 14.8) PD at 9:30 PM. Bumped plug to 2027 psi, held OK. Circ 68 sxs. 4/26/00 - Drilled out at 2:30 PM. WOC 41 hrs. Reduced hole to 7-7/8'' and resumed drilling.				
4/26/00 - Drilled out at 2:30 PM 5/24/00 - Reached TD of 13,02		ole to 7-778" and	resumed drilling.	
5/25/00 - Rigged up loggers.		ashed and ream	ed to bottom.	
5/26/00 – TOH. Tight hole at 12,966'. Stuck pipe. Spotted 100 bbls oil and worked pipe loose.				
5/27/00 – Rig up loggers and log. Logger's TD 13,025 ⁺ . 5/29/00 – Released rig at 1:00 PM.				
I hereby certify that the information i	above is true and complete to the	best of my knowled	dge and belief.	
SIGNATURE <u>1. 1.</u>	TITLE I	Engineering Tea	chnician _DATE_	<u>September 4, 2001</u>
Type or print name Susan He	rpin		Telephone	No. 505-748-1471
(This space for State use)			and DØ	
		en e		
APPPROVED BY Conditions of approval. if any:		<u></u>	<u> </u>	DATE DATE
Solutions of approval, if any.				\mathfrak{C}