

# INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true verticle depths shall be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

## INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

### Southeastern New Mexico

T. Anhy		T. Canyon	
T. Salt		T. Strawn	11421
B. Salt		T. Atoka	11586
T. Yates	3322	T. Miss	
T. 7 Rivers	3225	T. Devonian	
T. Queen		T. Silurian	
T. Grayburg		T. Montoya	
T. San Andres	4877	T. Simpson	
T. Glorieta	6337	T. McKee	
T. Paddock	6901	T. Ellenburger	
T. Blinebry		T. Gr. Wash	
T. Tubb	7567	T. Delaware Sand	
T. Drinkard	7702	T. Bone Springs	
T. Abo	8301	T.	
T. Wolfcamp	9617	T.	
T. Penn	10992	T.	
T. Cisco (Bough C)		T.	

### Northwestern New Mexico

T. Ojo Alamo	T. Penn "B"
T. Kirtland-Fruitland	T. Penn "C"
T. Pictured Cliffs	T. Penn "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzte
T. Base Greenhorn	T. Granite
T. Dakota	T.
T. Morrison	T.
T. Todilto	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn "A"	T.

## OIL OR GAS SANDS OR ZONES

No. 1, from \_\_\_\_\_ to \_\_\_\_\_  
 No. 2, from \_\_\_\_\_ to \_\_\_\_\_

No. 3, from \_\_\_\_\_ to \_\_\_\_\_  
 No. 4, from \_\_\_\_\_ to \_\_\_\_\_

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in the hole.

No. 1, from \_\_\_\_\_ to \_\_\_\_\_ feet  
 No. 2, from \_\_\_\_\_ to \_\_\_\_\_ feet  
 No. 3, from \_\_\_\_\_ to \_\_\_\_\_ feet

## LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	2020	2020	SALT/ANHYDRITE				
2020	3225	1205	SALT/ANHY/LIME				
3225	3322	97	SAND/DOLOMITE				
3322	4877	1555	DOLOMITE/SAND				
4877	6337	1460	DOLOMITE/ANHYDRITE				
6337	6901	564	SILTY DOLOMITE				
6901	7567	666	DOLOMITE/ANHYDRITE				
7567	7702	135	SILTY DOLOMITE				
7702	8301	599	DOLOMITE/ANHYDRITE				
8301	9617	1316	DOLOMITE/LIMESTONE				
9617	10992	1375	LIMESTONE/SHALE				
10992	11421	429	SHALE/LIMESTONE				
11421	11586	165	LIMESTONE				