

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form 1-163
Revised 1-1-97

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87411

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-35185

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

VA-604

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Lot 11

Unit Letter K

: 4000

Feet From The South

Line and

1980

Feet From The West

Line

Section 2

Township 16S

Range 35E

NMPM

Lea

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3993' GR

7. Lease Name or Unit Agreement Name

Field APK State Com

8. Well No.

4

9. Pool name or Wildcat

Wildcat Morrow

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Intermediate casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4695'. Reached TD at 6:00 PM 4-14-2001. Ran 114 joints of 8-5/8" 32# J-55 (4721.64') of casing set at 4692'. 1-regular guide shoe set at 4692'. Float collar set at 4649'. Cemented with 1050 sacks Interfill C and 1/4#/sack flocele (yield 2.46, weight 11.9). Tailed in with 250 sacks Class C with 2% CaCl2 (yield 1.32, weight 14.8). PD 10:45 AM 4-15-2001. Bumped plug to 1550 psi, OK. Circulated 92 sacks. WOC. Nipped up and tested to 5000# for 30 minutes, OK. Drilled out at 7:45 AM 4-17-2001. WOC 45 hours. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Rusty Klein

TITLE

Operations Technician

DATE

June 30, 2001

TYPE OR PRINT NAME

Rusty Klein

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY

PAUL F. KLEIN

PETROLEUM

TITLE

OWNER

APPROVED BY

DATE

1 2001

CONDITIONS OF APPROVAL, IF ANY: