

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-35185
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	VA-604
7. Lease Name or Unit Agreement Name	
Field APK State Com	
8. Well No.	4
9. Pool name or Wildcat	Wildcat Morrow
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	
3993' GR	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Lot 11 Unit Letter K : 4000 Feet From The South Line and 1980 Feet From The West Line
Section 2 Township 16S Range 35E NMMPM Lea County	10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3993' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Spud, conductor, resume drilling, surface casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 20" hole with rat hole machine at 10:30 AM 4-2-2001. Drilled to 40'. Set 40' of 16" conductor pipe. Cemented to surface. NOTE: Notified Sylvia with OCD-Hobbs. Resumed drilling a 14-3/4" hole at 2:45 AM 4-6-2001. NOTE: Notified Sylvia w/OCD-Hobbs of intent to resume drilling.

TD 405'. Reached TD at 9:00 AM 4-6-2001. Ran 9 joints of 11-3/4" 42# H-40 (408.81') of casing set at 405'. 1-Texas Pattern notched guide shoe set at 405'. Insert float set at 368'. Cemented with 265 sacks Class C with 2% CaCl2 (yield 1.32, weight 14.8). PD 1:30 PM 4-6-2001. Bumped plug to 600 psi, OK. Circulated 20 sacks. WOC. Nippled up rotating head. Drilled out at 9:00 AM 4-7-2001. WOC 19 hours and 30 minutes. Reduced hole to 11". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE June 30, 2001

TYPE OR PRINT NAME Rusty Klein

TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

ORIGINAL FILED BY
DATE
PETROLEUM ENGINEER