State of New Mexico

P.O. BOX 1980, HODDS NM 88240	finerals and Natural Resource		WELL API NO.		
DISTRICT II  P.O. Drawer DD, Artesia NM 88210	OIL CONSERVATION DIVISION P.O. Box 2088			<u> </u>	
	Santa Fe, New Mexico 87504-2088			30-025-35250 5. Indicate Type of Lease	
1000 Rio Brazos Rd., Aztec NM 87410			State X	FEE	
SUNDRY NOTICES AND REPORTS ON WELLS  (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"			7. Lease Name or Unit		
(FORM C-101) FOR SUC	H PROPOSALS.)		_		
OIL GAS WELL WELL OTHER  2. Name of Operator			Chevy AV	State Com	
Yates Petroleum Corporation				1	
3. Address of Operator  105 South 4th., Artesia, NM 88210 4. Well Location				9. Pool Name or Wildcat Eidson Morrow, North	
Unit Letter K : 1650 Feet From The	South Line at	nd <u>1650</u> Fe	et From The	West Line	
Section 13 Township T15S Rar	ige R34E NMP!	1		Lea county	
	ow whether DF, RKB, RT, GF 4056' GR	R, etc.)		Lea County	
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data					
NOTICE OF INTENTION TO:  PERFORM REMEDIAL WORK PLUG AND ABAN  TEMPORARILY ABANDON CHANGE PLANS  PULL OR ALTER CASING  OTHER  12. Describe Proposed or Completed Operation date of starting any proposed work) SEE	CASING  COMME  CASING  OTHER  CICLE 1103.	SUBSEQUENT  IAL WORK  INCE DRILLING OPNS  I TEST AND CEMENT JOB  Intermediate casing  etails, and give pertinenet of	ALTERING CASING PLUG AND ABANDI  dates, including es	timated	
9-24-01 - TD 11" hole @ 1:45 am. Rig p & run 110 jts 8-5/8" 32# (4606') casing, set @ 4600'. Regular guide					
shoe set @ 4590', float collar set @ 4546'. Cemented w/920 sx Interfill "C" (yld 2.41, wt 11.9). Tailed in					
with 250 sx Premium Plus "C" w/2% CaCl (yld 13.4, wt 14.8). Plug Down @ 10:00 pm 9-24-01. Bumped					
plug to 1300 psi, held OK. WOC.					
9-25-01 - Received verbal permission from Gary Wink, NMOCD, to drill @ 11:30 am. Drilled out @ 6:45 am.					
WOC 32 hrs 45 min. Reduced hole to 7-7/8" & resumed drilling.					
11-1-01 - rigged up casers & ran 222 jt report as follows: 222 jts 7" 26# SP110 Float collar set @ 9914.89. Cemented 1# salt + 2% HR-7 (yld 2.47, wt 11.5). 7 5# sk Gilsonite, 1# salt + .2% HR-7 (yld	-flush joint casing (9967 w/50 sx Super H modific 「ailed in w/200 sx Supel	.25) set @ 9962'. Reg ed w/.5% Halad-344, . · H modified W/.5% H	ular guide sho	e set @ 9962	
I hereby certify that the information above a true and complete to the	es of my knowledge and belief				
SIGNATURE ASMINA (	Lack TITLE	Operations Tech	ician DATE	10/25/01	
TYPE OR PRINT NAME Donna Clack			TELEPHO	ONE NO 505-748-1471	
(This space for State Use) APPROVED BY	TITLE ORIG	INAL SIGNED BY	DATE FF	D 1 4 2002	
CONDITIONS OF APPROVAL, IF ANY:	Pr	UL F. KAUTZ LEUM ENGINEER	DATE	B 1 4 2002	