Submit 3 Copies To Appropriate District Office <u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 811 South First, Artesia, NM 88210 <u>District III</u>	State of New Mexico Energy, Minerals and Natural Resources OIL CONSERVATION DIVISION 2040 South Pacheco Santa Fe, NM 87505		Form C-103 Revised March 25, 1999 WELL API NO. 30-025-35295 5. Indicate Type of Lease STATE FEE					
1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> 2040 South Pacheco, Santa Fe, NM 87505			6. State Oil & Gas Lease No.					
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well:				7. Lease Name or Unit Agreement Name:G.R. Hare's Ear				
Oil Well Gas Well 2. Name of Operator	Other Dry Hol	e		8. Well No.				
David H. Arrington Oil & Gas, In	с			1		1		
3. Address of Operator				9. Pool name or Wildcat				
P.O. Box 2071, Midland, Texas 79702				Townsend Permo Upper Penn				
4. Well Location								
Unit Letter P_: 455'	feet from theSo	uth	_ line and869'_	feet from the	Eastline			
Section 35	Township		Range 35E	NMPM	County Lea			
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 3940' GR								
	propriate Box to Inc	licate Na						
	ENTION TO: PLUG AND ABANDON		SUB REMEDIAL WOR	SEQUENT REF	PORT OF: ALTERING CASING	; 🗆		
	CHANGE PLANS		COMMENCE DR	RILLING OPNS. D PLUG AND				
PULL OR ALTER CASING	MULTIPLE COMPLETION		CASING TEST AND CEMENT JOB					
OTHER:			OTHER: Amer	nded P&A Report				
12. Describe proposed or completed of starting any proposed work). or recompilation.	l operations. (Clearly st SEE RULE 1103. For	tate all per Multiple (ctinent details, and g Completions: Attac	give pertinent dates, h wellbore diagram	including estimated d of proposed completion	ate on		
4/23/01- RIH with tbg & circ wel 4/24/01POH with tbg. Weld on 4/25-27/01- RIH with tbg to spot 5280'-5290'. Ran tbg 4/28/01- RIH & tag stub plug @ 2	pull nipple. Take & $25 \text{ sxs stub plug, coul}$ g to $5 \frac{1}{2}$ " casing stub (stretch red d not get @ 9040'.	below 5225'. RU Spot 40 sxs cem	U reverse unit & di ent plug. PUH.	rill out bridge @	ż		

- spot 50 sxs cment plug. 5/01/01-RIH & tag TOC @ 4660'. PUH & spot 40 sxs cement plug @ 2000'. PUH to 525' & spot 40 sxs cement plug surface casing shoe. 5/02/01-RIH & tag plug @ 370' & spot 10 sxs surface plug.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.									
SIGNATURE	_TITLE	Engineer	DA	ATE2/5/01					
Type or print name Chuck Sledge			Telephone No.	(915) 682-6685					
(This space for State use)									
APPPROVED BY Billy E. Fruhan	_TITLE_	COMPLIANCE OFFICE	<u>~ </u>	DATE					
Conditions of approval, if any		LINIOL DILLOL	7.4						
1									

GWW

ر ک