	SUNDR SUNDR	UNE STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT Y NOTICES AND REPORTS ON WELLS his form for proposals to drill or to re-enter rell. Use Form 3160-3 (APD) for such proposa		1625 N. Fre Hobbs, NM	88240 NM-LC0	OMB No. 1004-0135 Expires November 30, 2000		
1. Type of Well		PLICATE - Other instr		e side	<u> </u>	or CA/Agreement, Name and/or N		
		Other Proposed gas	s well Wally Frank,	Senior Ons	8. Well Na Maljamar	me and No. r "10" Federal #1		
2. Name of Operator Devon-SFS Operating, Inc.				552-4595	9. API We	11 No.		
a. Address 20 N. Broadway, Suite 1500, OKC, OK 73102			3b. Phone No. (inc (405)235-3611	lude area code )	30-025-3531710. Field and Pool, or Exploratory Area			
4 Location of W	ell ( Footage See	c., T., R., M., or Survey Descrip t O, Section 10-T17S-R	<sup>on )</sup> 2E, Lea Cnty, NM		Wildcat (Atoka) 11. County or Parish, State Lea County New Mexico			
12	. CHECK AP	PROPRIATE BOX(ES)	TO INDICATE NAT	TURE OF NOTICE, F	REPORT, O	R OTHER DATA		
TYPE OF SUI	BMISSION			TYPE OF ACTION				
<ul> <li>Notice of Inte</li> <li>Subsequent F</li> <li>Final Abando</li> </ul>		<ul> <li>Acidize</li> <li>Alter Casing</li> <li>Casing Repair</li> <li>Change Plans</li> <li>Convert to Injection</li> </ul>		_ •	bandon	<ul> <li>Water Shut-Off</li> <li>Well Integrity</li> <li>Other spud, setting casing strings, WOCU</li> </ul>		
If the proposal Attach the Bo following corr testing has bee	l is to deepen dire nd under which t pletion of the inv en completed. Fir	ectionally or recomplete horizon he work will be performed or pr volved operations. If the operation	tally, give subsurface loc ovide the Bond No. on fil on results in a multiple co	ations measured and true v e with BLM/BIA. Require mpletion or recompletion i	vertical depths or ed subsequent r in a new interva	ork and approximate duration the of all pertinent markers and zones eports shall be filed within 30 day al, a Form 3160-4 shall be filed on en completed, and the operator has		
If the proposal Attach the Bo following corr testing has bee determined the This well spue csg, set at 10	I is to deepen dire nd under which t pletion of the inv en completed. Fir at the site is ready d on 03-20-2 31'; cemente	ectionally or recomplete horizon he work will be performed or pr volved operations. If the operational Abandonment Notices shall y for final inspection.) 2001 at 1600 hrs and drl ed w/563 sx 35/65 Pozn	tally, give subsurface loc ovide the Bond No. on fil on results in a multiple co be filed only after all requ d a 17 1/2" hole to hix "C" + 300 sx Cla	ations measured and true v e with BLM/BIA. Require mpletion or recompletion i irements, including reclam 1032'. On 03-21-24 ass "C"; TOC at sur	vertical depths of ed subsequent r in a new interva- nation, have bee 001 ran 24 face. WO0	of all pertinent markers and zones eports shall be filed within 30 day al, a Form 3160-4 shall be filed on en completed, and the operator has jts 13 3/8" 48# H-40 ST8 C 23 hrs.		
If the proposal Attach the Bo following corr testing has bee determined the This well spue csg, set at 10 Drld 12 1/4" h Pozmix "C" + Began drlg 7 Hughes ran E On 05-07-200 Pozmix "C"; s	I is to deepen dire nd under which t apletion of the inven en completed. Fir at the site is ready d on 03-20-2 31'; cemente nole to 4610'. 625 sx 60/40 7/8" hole. R Dual Laterlog 01 ran 303 jts stage 2 w/425	ectionally or recomplete horizon he work will be performed or pr volved operations. If the operational Abandonment Notices shall y for final inspection.) 2001 at 1600 hrs and drl ed w/563 sx 35/65 Pozn	tally, give subsurface loc ovide the Bond No. on fil on results in a multiple co be filed only after all requ d a 17 1/2" hole to nix "C" + 300 sx Cli 08 jts 8 5/8" 32# J-5 urface. WOC 36 h 830 hrs 04-27-200 Z-Densilog/Compo csg, set at 12,799	ations measured and true v e with BLM/BIA. Require mpletion or recompletion i irements, including reclarr 1032'. On 03-21-24 ass "C"; TOC at sur 55 LT&C csg, set at ars. 1. Circ'd, washed a ensated Neutron/Gf	vertical depths of ed subsequent n in a new interva- nation, have bee 001 ran 24 face. WOO 4609'; cerr nd reamed R logs. ; cemented	of all pertinent markers and zones eports shall be filed within 30 day al, a Form 3160-4 shall be filed on en completed, and the operator has jts 13 3/8" 48# H-40 ST& C 23 hrs. hented w/1500 sx 35/65 . 05-04-2001 Baker		
If the proposal Attach the Bo following corr testing has bee determined the This well spue csg, set at 10 Drld 12 1/4" h Pozmix "C" + Began drlg 7 Hughes ran E On 05-07-200 Pozmix "C"; s Released rig	I is to deepen dire nd under which t pletion of the invention en completed. Fir at the site is ready d on 03-20-2 (31'; cementer nole to 4610'. 625 sx 60/40 7/8" hole. R Dual Laterlog 01 ran 303 jts stage 2 w/425 at 1400 hrs ( fy that the foregoined/Typed)	ectionally or recomplete horizon he work will be performed or pr volved operations. If the operational Abandonment Notices shall by y for final inspection.) 2001 at 1600 hrs and drl ed w/563 sx 35/65 Pozn . On 04-01-2001 ran 10 0 Pozmix "C"; TOC at s leached TD 12,800' at 1 J/GR and Compensated s 5 1/2" 17# L-80 LT&C 5 sx Poz "C" + 100 sx C	tally, give subsurface loc ovide the Bond No. on fil on results in a multiple co be filed only after all requ d a 17 1/2" hole to nix "C" + 300 sx Cl b8 jts 8 5/8" 32# J-5 urface. WOC 36 h 830 hrs 04-27-200 Z-Densilog/Compo csg, set at 12,799 class "H".	ations measured and true v e with BLM/BIA. Require mpletion or recompletion i irements, including reclarr 1032'. On 03-21-24 ass "C"; TOC at sur 55 LT&C csg, set at 1. Circ'd, washed a ensated Neutron/GF ' w/DV tool at 6382'.	vertical depths of ad subsequent r in a new interva- nation, have bee 001 ran 24 face. WOO 4609'; cerr nd reamed. R logs. ; cemented	of all pertinent markers and zones eports shall be filed within 30 day al, a Form 3160-4 shall be filed on en completed, and the operator has jts 13 3/8" 48# H-40 ST8 C 23 hrs. hented w/1500 sx 35/65 . 05-04-2001 Baker : stage 1 w/1500 sx PTED FOR RECORD SEP 2 6 2001		
If the proposal Attach the Bo following corr testing has bee determined the This well spuce csg, set at 10 Drld 12 1/4" h Pozmix "C" + Began drlg 7 Hughes ran D On 05-07-200 Pozmix "C"; s Released rig	I is to deepen dire nd under which t pletion of the invention en completed. Fir at the site is ready d on 03-20-2 (31'; cemented nole to 4610'. 625 sx 60/40 7/8" hole. R Dual Laterlog 01 ran 303 jts stage 2 w/42! at 1400 hrs ( fy that the foregoined ted/Typed ) Graham	ectionally or recomplete horizon he work will be performed or pr volved operations. If the operational Abandonment Notices shall by y for final inspection.) 2001 at 1600 hrs and drl ed w/563 sx 35/65 Pozn . On 04-01-2001 ran 10 0 Pozmix "C"; TOC at s eeached TD 12,800' at 1 J/GR and Compensated s 5 1/2" 17# L-80 LT&C 5 sx Poz "C" + 100 sx C 05-08-2001. WOCU.	tally, give subsurface loc ovide the Bond No. on fil on results in a multiple co be filed only after all requ d a 17 1/2" hole to nix "C" + 300 sx Cli 08 jts 8 5/8" 32# J-{ urface. WOC 36 h 830 hrs 04-27-200 Z-Densilog/Compo csg, set at 12,799 class "H". Title Eng Date	ations measured and true v e with BLM/BIA. Require mpletion or recompletion i irements, including reclarr 1032'. On 03-21-24 ass "C"; TOC at sur 55 LT&C csg, set at 1. Circ'd, washed a ensated Neutron/GF ' w/DV tool at 6382'.	vertical depths of ad subsequent r in a new interva- nation, have bee 001 ran 24 face. WOO 4609'; cerr nd reamed. R logs. ; cemented	of all pertinent markers and zones eports shall be filed within 30 day al, a Form 3160-4 shall be filed on en completed, and the operator has jts 13 3/8" 48# H-40 ST8 C 23 hrs. hented w/1500 sx 35/65 . 05-04-2001 Baker <u>: stage 1 w/1500 sx</u> PTED FOR RECORD SEP 2 6 2001		
If the proposal Attach the Bo following corr testing has bee determined the This well spuce csg, set at 10 Drld 12 1/4" h Pozmix "C" + Began drlg 7 Hughes ran D On 05-07-200 Pozmix "C"; s Released rig	I is to deepen dire nd under which t pletion of the invention en completed. Fir at the site is ready d on 03-20-2 (31'; cemented nole to 4610'. 625 sx 60/40 7/8" hole. R Dual Laterlog 01 ran 303 jts stage 2 w/42! at 1400 hrs ( fy that the foregoined ted/Typed ) Graham	ectionally or recomplete horizon he work will be performed or pr volved operations. If the operational Abandonment Notices shall by for final inspection.) 2001 at 1600 hrs and dri ed w/563 sx 35/65 Pozn . On 04-01-2001 ran 10 0 Pozmix "C"; TOC at s teached TD 12,800' at 1 J/GR and Compensated s 5 1/2" 17# L-80 LT&C 5 sx Poz "C" + 100 sx C 05-08-2001. WOCU.	tally, give subsurface loc ovide the Bond No. on fil on results in a multiple co be filed only after all requ d a 17 1/2" hole to nix "C" + 300 sx Cli 08 jts 8 5/8" 32# J-5 urface. WOC 36 h 830 hrs 04-27-200 Z-Densilog/Compo csg, set at 12,799 Class "H".	ations measured and true v e with BLM/BIA. Require mpletion or recompletion i irements, including reclarr 1032'. On 03-21-24 ass "C"; TOC at sur 55 LT&C csg, set at 1. Circ'd, washed a ensated Neutron/GF ' w/DV tool at 6382'.	vertical depths of ad subsequent r in a new interva- nation, have bee 001 ran 24 face. WOO 4609'; cerr nd reamed. R logs. ; cemented ACCET	of all pertinent markers and zones eports shall be filed within 30 day al, a Form 3160-4 shall be filed on en completed, and the operator has jts 13 3/8" 48# H-40 ST8 C 23 hrs. hented w/1500 sx 35/65 . 05-04-2001 Baker : stage 1 w/1500 sx PTED FOR RECORD SEP 2 6 2001		
If the proposal Attach the Bo following corr testing has bee determined the This well spuce csg, set at 10 Drld 12 1/4" h Pozmix "C" + Began drlg 7 Hughes ran D On 05-07-200 Pozmix "C"; s Released rig	I is to deepen dire nd under which t pletion of the invention en completed. Fir at the site is ready d on 03-20-2 (31'; cemented nole to 4610'. 625 sx 60/40 7/8" hole. R Dual Laterlog 01 ran 303 jts stage 2 w/42! at 1400 hrs ( fy that the foregoined ted/Typed ) Graham	ectionally or recomplete horizon he work will be performed or pr volved operations. If the operational Abandonment Notices shall by for final inspection.) 2001 at 1600 hrs and dri ed w/563 sx 35/65 Pozn . On 04-01-2001 ran 10 0 Pozmix "C"; TOC at s teached TD 12,800' at 1 J/GR and Compensated s 5 1/2" 17# L-80 LT&C 5 sx Poz "C" + 100 sx C 05-08-2001. WOCU.	tally, give subsurface loc ovide the Bond No. on fil on results in a multiple co be filed only after all requ d a 17 1/2" hole to nix "C" + 300 sx Cli 08 jts 8 5/8" 32# J-5 urface. WOC 36 h 830 hrs 04-27-200 Z-Densilog/Compo csg, set at 12,799 Class "H".	ations measured and true v e with BLM/BIA. Require mpletion or recompletion i irements, including reclam 1032'. On 03-21-24 ass "C"; TOC at sur 55 LT&C csg, set at ars. 1. Circ'd, washed a ensated Neutron/GI ' w/DV tool at 6382', w/DV tool at 6382', jineering Tech.	vertical depths of ed subsequent n in a new interva- nation, have bee 001 ran 24 face. WOO 4609'; cerr nd reamed R logs. ; cemented PET	of all pertinent markers and zones eports shall be filed within 30 day al, a Form 3160-4 shall be filed on en completed, and the operator has jts 13 3/8" 48# H-40 ST8 C 23 hrs. hented w/1500 sx 35/65 . 05-04-2001 Baker : stage 1 w/1500 sx PTED FOR RECORD SEP 2 6 2001		
If the proposal Attach the Bo following corr testing has bee determined the This well spuce csg, set at 10 Drld 12 1/4" h Pozmix "C" + Began drlg 7 Hughes ran E On 05-07-200 Pozmix "C"; s Released rig 14. I hereby certif Name (Print Candace R. C Signature	I is to deepen dire nd under which t and under which t pletion of the inver- encompleted. Fir at the site is ready d on 03-20-2 (31'; cementer nole to 4610'. 625 sx 60/40 7/8" hole. R Dual Laterlog 01 ran 303 jts stage 2 w/42 at 1400 hrs ( fy that the foregoine ted/Typed) Graham	ectionally or recomplete horizon he work will be performed or pr volved operations. If the operational Abandonment Notices shall by for final inspection.) 2001 at 1600 hrs and dri ed w/563 sx 35/65 Pozn . On 04-01-2001 ran 10 0 Pozmix "C"; TOC at s teached TD 12,800' at 1 J/GR and Compensated s 5 1/2" 17# L-80 LT&C 5 sx Poz "C" + 100 sx C 05-08-2001. WOCU.	tally, give subsurface loc ovide the Bond No. on fil on results in a multiple co be filed only after all requ d a 17 1/2" hole to nix "C" + 300 sx Cli 08 jts 8 5/8" 32# J-5 urface. WOC 36 h 830 hrs 04-27-200 Z-Densilog/Compo csg, set at 12,799 csg, set at 12,799 class "H". Title Eng Date 09/* FOR FEDERAL OF	ations measured and true v e with BLM/BIA. Require mpletion or recompletion i irements, including reclam 1032'. On 03-21-24 ass "C"; TOC at sur 55 LT&C csg, set at ars. 1. Circ'd, washed a ensated Neutron/GF ' w/DV tool at 6382'. w/DV tool at 6382'. gineering Tech. 17/2001 RETATE OFFICE US	vertical depths of ed subsequent n in a new interva- nation, have bee 001 ran 24 face. WOO 4609'; cerr nd reamed R logs. ; cemented PET	of all pertinent markers and zones eports shall be filed within 30 day al, a Form 3160-4 shall be filed on en completed, and the operator has jts 13 3/8" 48# H-40 ST8 C 23 hrs. hented w/1500 sx 35/65 . 05-04-2001 Baker : stage 1 w/1500 sx PTED FOR RECORD SEP 2 6 2001 LES BABYAK IROLEUM ENGINEER		

10

2001 SEP 20 AN 9: 12

BECEIVED

the grants

÷

Form 3160-3 (December 1990)	DEPAR	•	STATES <sup>Now M</sup>	OD Secon	her instru on	<b>E</b> *	Form approved.			
			ND MANAGEMENT	revers	e side)	SLEASE DESI	IGNATION AND SERI	AL NO		
APPLICATION FOR PERMIT TO DRILL OR DEEPEN							NM-LC059576			
AF	PLICATIO	6.IF INDIAN, ALLOTTEE OR TRIBE NAME								
la TYPE OF WORK:	DRILI		DEEPEN							
b. TYPE OF WELL:						7.UNIT AGRE	EMENT NAME			
OIL WELL	GAS WELL	Other	SINGLE ZONE	MULTIPLE ZONE		8 FARM OR L	EASE NAME, WELL N	10		
2 NAME OF OPERAT			MALJAMAR "10" FEDERAL #1							
		SFS OPERATING	J, INC.	······		9.API WELL NO.				
3. ADDRESS AND TE			E 1500, OKC, OK 73102 (	(405) 235-3611		30-025-3.53/7				
4. LOCATION OF WE	LL (Report loca	ation clearly and in a	accordance with any State requir	rements)*	·	10.FIELD AND	POOL, OR WILDCA	Г		
At surface 660' H	FSL & 1530' FI	l	Maljamar (Morrow)							
No. 1 1	( )		Lea			11.SEC.,T.,R.,M.,OR BLOCK AND SURVEY OR AREA				
At top proposed prod	. zone (same)	)				Unit O Section 10, T17S, R32E				
14.DISTANCE IN MILES AN	D DIRECTION FR	OM NEAREST TOWN (	OR POST OFFICE*			12. COUNTY		13. STATE		
Approximately 1 miles	south of Malija	mar, New Mexico,	on Hwy 82			Lea Cour	nty	New Mexico		
15.DISTANCE FROM PROPO		· · · · · · · · · · · · · · · · · · ·	16.NO. OF ACRES IN LEASE				17.NO. OF ACRES			
LOCATION TO NEARES	ST		320				TO THIS WELL			
PROPERTY OR LEASE I (Also to nearest drlg, unit lir		660'					320			
18.DISTANCE FROM PROPO TO NEAREST WELL, DE			19.PROPOSED DEPTH				20.ROTARY OR CA	ABLE TOOLS*		
OR APPLIED FOR, ON T			12,700'	12,700'			Rotary 22. APPROX. DATE WORK WILL START*			
21.ELEVATIONS (Show when GL 4108'		· · ·				Dece	mber , 2000			
23. SIZE OF HOLE	GRADE	SIZE OF CASING	PROPOSED CASING AND WEIGHT PER FOOT	CEMENTING	PROGRAM SETTING DEPTH	T	QUANTITY	OF CEMENT		
17 1/2"	H-40	13 3/8"	48.0	ITNESS	·650' 1025'	a	pprox 600 sx (est			
12 1/4"	J-55	8 5/8"	32.0		4,600'		pprox 1900 sx (es			
7 7/8"	L-80	5 1/2"	17.0		2,700'		pprox 700 sx (est			
plugged and abandor Drilling Program Surface Use and Ope Exhibits #1 = Blowo Exhibits #2 = Locatio Exhibits #3 = Road 1 Exhibit #4 = Wells V Exhibits #5 = Produc Exhibits #5 = Produc Exhibit #6 = Rotary Exhibit #7 = Casing H <sub>2</sub> S Operating Plan Archeological cleare	erating Plan but Prevention I on and Elevatio Map and Topo Within 1 Mile f ction Facilities Rig Layout Design ance report	I regulations. Progr Equipment n Plat SENERAL S SENERAL RE SPECIAL STR	The and a porti UBJECT TO Leas CUIREMENTS AN PULATIONS BLM	undersigned acc restrictions cond tons thereof, as the et al. NM-LC05 al Description: d Coverage: Na 4 Bond #: UT-1	cons are outlined in <b>CONTROLL</b> cepts all applicable cerning operations described below 9573 E/2 Section 10-T1 ationwide 1195	the followin <b>D WA</b> e terms, cond conducted o 7S-R32E OPER. PROPI POOL EFF. D	exhibits and atta <b>TER BASH</b> bitions, stipulation in the leased land . OGRID NO ERTY NO.2 CODE DATE / 2	achments. s or: 2, 20305 2, 7049 2, 7049		
IN ABOVE SPACE DI proposal is to drill or d 24.	LSCRIBE PRC leepen directio	nally, give pertinen	M: If proposal is to deepen, gi t data on subsurface locations	and measured a	and true vertical d		). <u>50-02</u>	5-353/7		
						٠				
$\cap$		$\sim N$ /	Can	dace R. Grahar	n					

TITLE Engineering Technician

DATE November 10, 2000

\*(This space for Federal or State office use)

PERMIT NO. \_\_\_\_\_ APPROVAL DATE \_\_\_\_\_

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. **CONDITIONS OF APPROVAL, IF ANY:** 

APPROVED BY\_\_\_\_\_

500

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

See Instructions On Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent Q mp statements or representations as to any matter within its jurisdiction



•