

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO.

30 - 025 - 35364

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

V-4882-1, V-4884-1

7. Lease Name or Unit Agreement Name:

E.L. Harrod

8. Well No.

1

9. Pool name or Wildcat

Townsend Morrow

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

Nadel and Gussman Permian, L.L.C. OGRID # 155615

3. Address of Operator

601 N Marienfeld, Suite 508, Midland, Texas 79701

4. Well Location

Unit Letter U : 660' feet from the South line and 660' feet from the West line

Section 5 Township 16-S Range 35-E NMPM Lea County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

4052' GL, 4070' KB

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER ☐

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

Notice of spud and setting surface casing:

1. MIRU Patterson Rig #47. Spud 17 1/2" hole at 2:00 AM on 4/27/01.
2. Drilled to 409'. Set 13-3/8", 48# H-40 casing at 409'.
3. Cemented w/ 435 sx "C" with 2% CaCl @ 15.2 ppg. Circulated 52 sx to reserve pit.
4. Cut off 13-3/8" casing. Test BOP and valves. TIH with 12 1/4" bit and drilled shoe and cement. Resumed drilling intermediate hole section.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE Operations Engineer DATE 5-1-01

Type or print name Robert McNaughton

Telephone No. 915 - 682 - 4429

(This space for State use)

APPROVED BY _____ TITLE _____ ORIGINAL COPIES OF _____ DATE _____

Conditions of approval, if any:

GARY BROWN
FIELD REPRESENTATIVE

