

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-35377
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	VO-4837
7. Lease Name or Unit Agreement Name	
Avian AYA State	
8. Well No.	1
9. Pool name or Wildcat	Wildcat Mississippian

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter P : 850 Feet From The South Line and 660 Feet From The East Line Section 20 Township 15S Range 32E NMMPM Lea County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4315' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: Intermediate casing & cement <input checked="" type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4000'. Reached TD at 12:15 AM 3-10-2001. Ran 97 joints of 8-5/8" 32# J-55 (4010.24') of casing set at 4000'. 1-regular guide shoe set at 4000'. Float collar set at 3957'. Cemented with 975 sacks Interfill C, 1/4#/sack flocele (yield 2.46, weight 11.9). Tailed in with 200 sacks Premium Plus and 2% CaCl2 (yield 1.34, weight 14.8). PD 3:00 PM 3-10-2001. Circulated 207 sacks. WOC. Nippled up and tested to 5000 psi for 30 minutes, OK. Drilled out at 7:00 AM 3-12-2001. WOC 40 hours. Reduced hole to 7-7/8". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE May 29, 2001
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY _____ TITLE Orig. Signed by Paul Reutz Geologist DATE _____
CONDITIONS OF APPROVAL, IF ANY: