Submit 3 Copies To Appropriate District		
	State of New Mexico	Form C-103
Office District I	Energy, Minerals and Natural Resou	urces Revised March 25, 1999
625 N. French Dr., Hobbs, NM 88240		WELL API NO.
<u>District II</u> 11 South First, Artesia, NM 88210	OIL CONSERVATION DIVISI	ON 30-025-35388
District III	1220 South St. Francis Dr.	5. Indicate Type of Lease
000 Rio Brazos Rd., Aztec, NM 87410	Santa Fe, NM 87505	STATE     X     FEE       6.     State Oil & Gas Lease No.
<u>District IV</u> 220 S. St. Francis Dr., Santa Fe, NM		
7505		VO-4836
DO NOT USE THIS FORM FOR PROPOSA	ES AND REPORTS ON WELLS ALS TO DRILL OR TO DEEPEN OR PLUG BACK T ATION FOR PERMIT" (FORM C-101) FOR SUCH	7. Lease Name or Unit Agreement Name: TO A Alar AYL State
Oil Well Gas Well X	Other	
. Name of Operator		7. Well No.
Yates Petroleum Corpore	ation	#1
. Address of Operator	8. Pool name or Wildcat	
105 S. 4 <sup>th</sup> Street Artesia, NM 88210		Wildcat Mississippian
. Well Location		
Unit Letter <b>P: 660</b>	<b>)</b> feet from the <b>South</b> line and _	660 feet from the <b>East</b> line
	Township 15S Range 32E	
	10. Elevation (Show whether DR, RKB, R	
	4337' GR	
11 Check At	ppropriate Box to Indicate Nature of	Notice, Report or Other Data
NOTICE OF IN		SUBSEQUENT REPORT OF:
NOTICE OF IN		
ERFORM REMEDIAL WORK	PLUG AND ABANDON	
		ENCE DRILLING OPNS.
ULL OR ALTER CASING	MULTIPLE CASING COMPLETION CEMEN	
THER:		X X X X X X X X X X X X X X X X X X X
starting any proposed work). SEE Frecompilation.	RULE 1103. For Multiple Completions: At	, and give pertinent dates, including estimated date of ttach wellbore diagram of proposed completion of LKD
5/19/01 – Drilled to 10,097'. W 5/21/01 – Work stuck pipe, wo	ould not come free. Back off drill coll	lars. Left 6 6" drill collars, 2 1890 combo
short drill collar and bit in hole 5/22-5/26/01 – Top of fish 9916 kick off.	e. 5', bottom 10,097'. Try to recover fish	n, no recovery. Prepto set cement plug and
5/27/01 – TIH open ended. Pu at 9600', WOC.		CD-31. PD at 10:30 AM. TIH and tag cement
	nent plug to 9751'. Drill out at 11:00 A	AM. WOC 24 hours 30 mins. hole motor. Drilled to 9887', 50% cement, 50%
5/28/01 – Dress off top of cerr 5/31/01 – Drilled to 9794', rear	med to bottom. Picked up straight h	
5/31/01 – Drilled to 9794', rear lime. 6/1/01 - Set cement plug #2 (	at 9865' with 170 sxs H + .2% CD-31. Pl	
5/31/01 – Drilled to 9794', rear lime. 6/1/01 - Set cement plug #2 ( 6/2/01 – Tagged TOC at 9500	at 9865' with 170 sxs H + .2% CD-31. Pl '. Drilled cement 9500-9640'.	D at 10:15 PM. WOC.
5/31/01 – Drilled to 9794', rear lime. 6/1/01 - Set cement plug #2 ( 6/2/01 – Tagged TOC at 9500	at 9865' with 170 sxs H + .2% CD-31. Pl	D at 10:15 PM. WOC.
5/31/01 – Drilled to 9794', rear lime. 6/1/01 - Set cement plug #2 of 6/2/01 – Tagged TOC at 9500 I hereby certify that the information	at 9865' with 170 sxs H + .2% CD-31. Pl '. Drilled cement 9500-9640'. n above is true and complete to the best of m	D at 10:15 PM. WOC.
5/31/01 – Drilled to 9794', rear lime. 6/1/01 - Set cement plug #2 c 6/2/01 – Tagged TOC at 9500 I hereby certify that the information SIGNATURE	at 9865' with 170 sxs H + .2% CD-31. Pl Drilled cement 9500-9640'. n above is true and complete to the best of m 	D at 10:15 PM. WOC. ny knowledge and belief. r <b>ing Technician</b> DATE <u>March 1, 2002</u> Telephone No. <b>505-748-147</b> 1
5/31/01 – Drilled to 9794', rear lime. 6/1/01 - Set cement plug #2 of 6/2/01 – Tagged TOC at 9500 I hereby certify that the information SIGNATURE <u>Justin Hu</u> Type or print name <b>Susan He</b> (This space for State use)	at 9865' with 170 sxs H + .2% CD-31. Pl '. Drilled cement 9500-9640'. n above is true and complete to the best of m TITLE Engineer erpin Approved	D at 10:15 PM. WOC. ny knowledge and belief. ring Technician DATE <u>March 1, 2002</u> Telephone No. <b>505-748-147</b> 1 as to plugging of the Well Bore.
5/31/01 – Drilled to 9794', rear lime. 6/1/01 - Set cement plug #2 c 6/2/01 – Tagged TOC at 9500 I hereby certify that the information SIGNATURE	at 9865' with 170 sxs H + .2% CD-31. Pl '. Drilled cement 9500-9640'. n above is true and complete to the best of m TITLE Engineer erpin Approved Liability un TITLEsurface res	D at 10:15 PM. WOC. ny knowledge and belief.

.. ----

Yates Petroleum Corporation Alar AYL State #1 API - 30-025-35388 Section 19 T15S R32E Lea County, NM

## Describe proposed or completed operations (continued):

6/3/-6/9/01 - Drill to 10,083'. Run DST #1 (Cisco) 9950-10,083'. 6/11/01 - Run DST #2 (Cisco) 10,082-10,091'. 6/26/01 - Drill to 12,580'. Run open hole logs. Logger's TD 12,579'. Wait on orders. 6/27/01 - Drilled to 12,616'. run DST #3 (Morrow) 12,575-12,616'. 6/29/01 - TD 7-7/8" hole at 12:30 PM at 12,810'. 6/30/01 - Run logs. Logger's TD 12,790'. Received verbal permission from Jerry Wink with NMOCD to set cement plugs. Set cement plug at 12,792' with 35 sxs H + 5# LCM-1 + .2% R-3. Set cement plug at 11,584' with 25 sxs H + 5# LCM-1 + .2% R-3. Set cement plug at 10,072' with 50 sxs H + 5# LCM-1 + .2% R-3. WOC. 7/1/01 – TIH – did not tag plug at 10,072'. Set cement plug at 10,072' with 60 sxs Premium + 5 pps gilsonite + .2% HR-7. WOC. TIH - did not tag. Circulate, no fluid loss. Set cement plug at 10,072' with 60 sxs H + 5# LCM-1 + .2% R-3. 7/3/01 – Run Gyro survey. Spot cement kick off plug at 8900-8400' with 360 sxs H. 7/4/01 - TIH to 8901', did not tag cement. Set cement plug at 8901' with 400 sxs H + .9%R-3. 7/5/01 - Tag cement at 8368'. Directionally drill. 7/11/01 - Run DST #4 (Wolfcamp) 9004-9150'. 7/20/01 - Run DST #5 (Wolfcamp) 9794-9932'. 7/22/01 - Reached TD of 7-7/8" directional hole at 9982'. Work stuck pipe and wait on orders. 7/23/01 – Received verbal permission from Gary Wink with NMOCD to set cement pluas. Set cement plug at 9961' with 35 sxs H. (TD-9861') Set cement plug at 7735' with 25 sxs H. (7735-7635') Set cement plug at 5260' with 25 sxs H (5260-5160') Set cement plug at 4050' with 50 sxs H + 2% CaCl2. WOC. TIH to tag, did not tag. 3455 Set cement plug at 4050' with 50 sxs H + 2% CaCl2. WOC. TIH and tag at 3881'. 7/24/01 - Set cement plug at 1934' with 25 sxs H. 128 29 3031 Set cement plug at 430' with 25 sxs H. MAR 2002 Set cement plug #7 at 62' with 10 sxs H. -IVED Rig released at 2:45 PM. Hobbs 0CD

(505) 746-6124 Office (505) 365-6414 Cellular (505) 748-8761 Fax



Post Office Box 1122 1908 South First Street Artesia, New Mexico 88211-1122

 Date
 Invoice #

 3/25/2002
 10459

**Bill To** 

YATES PETROLEUM CORP 105 S 4TH ST ARTESIA NM 88210

Authorization JIM KROGMAN		Terms JK 103-0343	Location ALAR "AYL" ST #1	
	3/21/02 PULLED WIRE AND POSTS, I BROKE OUT DRILLING PITS IN PITS, RIPPED PITS, PULLI WALKED PITS DOWN; PICKE PASTURE AND ON LOCATIO	AND MIXED MUD; PUSHED ED ALL PLASTIC AND ED UP ALL TRASH IN		
12	DOZER HOURS @		90.00	1,080.00
12	DOZER HOURS @		90.00	1,080.00
12	DOZER HOURS @		90.00	1,080.00
13	DOZER HOURS @		90.00	1170.00 2232425262
14	CREW HOURS @	IK	65.00 D	910.60
BLM S	BLM SEED	JK 920490	186.50	S 5 7 186.00
	DUMP FEE Sales Tax	920 440	110-90 6.3125%	5 5 110.00 E 73 354.5
			C.C.	11101682940

Subtotal

\$5,616.00

\$5,970.51

Total

Chank You For Your Business!