

DISTRICT I
P.O. Box 1980, Hobbs NM 88240

DISTRICT II
811 South First, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd, Aztec, NM 87410

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, New Mexico 87505

| |
|---|
| WELL API NO. 30-025-35763 |
| 5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/> |
| 6. State Oil & Gas Lease No. V-5013 |
| 7. Lease Name or Unit Agreement Name Yankees State |
| 8. Well No. 1 |
| 9. Pool name or Wildcat Kemnitz; Atoka-Morrow, South |
| 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4182 GR |

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS).

1. Type Of Well:
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator
Mack Energy Corporation


3. Address of Operator
P.O. Box 960, Artesia, NM 88211-0960

4. Well Location
Unit Letter H : 1980 Feet From The North Line and 660 Feet From The East Line
Section 23 Township 16S Range 33E NMPM Lea County

| | | | |
|---|---|---|---|
| 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data | | | |
| NOTICE OF INTENTION TO: | | SUBSEQUENT REPORT OF: | |
| PERFORM REMEDIAL WORK <input type="checkbox"/> | PLUG AND ABANDON <input type="checkbox"/> | REMEDIAL WORK <input type="checkbox"/> | ALTERING CASING <input type="checkbox"/> |
| TEMPORARILY ABANDON <input type="checkbox"/> | CHANGE PLANS <input type="checkbox"/> | COMMENCE DRILLING OPNS. <input type="checkbox"/> | PLUG AND ABANDONMENT <input type="checkbox"/> |
| PULL OR ALTER CASING <input type="checkbox"/> | | CASING TEST AND CEMENT JOB <input type="checkbox"/> | |
| OTHER: <input type="checkbox"/> | | OTHER: <input checked="" type="checkbox"/> | Spud, and cement casings |

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12/13/2001 Spud 17 1/2" hole.
12/14/2001 TD 17 1/2" hole @ 350', RIH w/13 3/8" H-40 ST&C 48# J-55 7 joints @ 342', Cemented w/350sx Class C, 2% CC circ 90sx. Plug down 7:00 PM. WOC 18 hours tested casing to 1800# for 30 minutes, held OK.
12/23/2001 TD 12 1/4" hole @ 4440', RIH w/103 joints 8 5/8" 32# J-55 ST&C landed @ 4440', Cemented w/1200sx 35/65/6, 1/4# CF, 5% salt, tail in w/200sx Class C, 2% CC circ 150sx. WOC 12 hours tested casing to 600# for 20 minutes, held OK.
01/27/2002 13,550' TD well @ 4:00 AM.
01/28/2002 Log well.
01/30/2002 RIH w/5 1/2" LT&C 17# 310 joints S-95 & N-80 set @ 13,550', Cemented 1st stage w/1500sx Super C Mod, 75% FL52, 75% FL25, 1% KCL, 2nd stage 1500sx 65/35/6 C, tail in w/200sx Class H, circ 280sx. Plug down 12:15 PM. WOC 12 hours tested casing to 600# for 20 minutes, held OK.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jerry W. Sherrell TITLE Production Clerk DATE 2/26/02

TYPE OR PRINT NAME Jerry W. Sherrell TELEPHONE NO. 748-1288

(This space for State Use)

APPROVED BY _____ TITLE ORIGINAL SIGNED BY
PAUL F. KAUTZ
PETROLEUM ENGINEER

CONDITIONS OF APPROVAL, IF ANY: MAR 01 2002