

Submit 3 Copies To Appropriate District Office  
 District I  
 1625 N. French Dr., Hobbs, NM 88240  
 District II  
 1301 W. Grand Ave., Artesia, NM 88210  
 District III  
 1000 Rio Brazos Rd., Aztec, NM 87410  
 District IV  
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
 Energy, Minerals and Natural Resources

Form C-103  
 Revised March 25, 1999

OIL CONSERVATION DIVISION  
 1220 South St. Francis Dr.  
 Santa Fe, NM 87505

WELL API NO.  
 30-025-35793

5. Indicate Type of Lease  
 STATE  FEE

6. State Oil & Gas Lease No.  
 V-6391

**SUNDRY NOTICES AND REPORTS ON WELLS**  
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
 Oil Well  Gas Well  Other

2. Name of Operator  
 MANZANO OIL CORPORATION

3. Address of Operator  
 P.O. BOX 2107 - ROSWELL, NM 88202-2107 (505) 623-1996

4. Well Location  
 Unit Letter 1/A: 660 feet from the NORTH line and 660 feet from the EAST line  
 Section 6 Township 17S Range 33E NMPM LEA County

7. Lease Name or Unit Agreement Name:  
 Johnny State

8. Well No.  
 1

9. Pool name or Wildcat  
 Kennnitz Wolfcamp, West

10. Elevation (Show whether DR, RKB, RT, GR, etc.)  
 4245' KB

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK  PLUG AND ABANDON   
 TEMPORARILY ABANDON  CHANGE PLANS   
 PULL OR ALTER CASING  MULTIPLE COMPLETION   
 OTHER:

SUBSEQUENT REPORT OF:

- REMEDIAL WORK  ALTERING CASING   
 COMMENCE DRILLING OPNS.  PLUG AND ABANDONMENT   
 CASING TEST AND CEMENT JOB   
 OTHER:

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

- TD 11" hole @ 4520' 2/5/02 - Run 102jts (4526') 8 5/8" 32#/ft J55 casing + 10 centralizers to TD - RU Halliburton & cement w/1300sx Class "C" cement (weight=11.9#/gl / yield=2.41ft/sk) + 250sx Class "C" cement + 2% CaCl (weight=14.8#/gl / yield=1.34ft/sk), Plug down @ 11:30a.m. 2/6/02, circulate 70sx cement to reserve pits
- Cut off casing & weld on wellhead, test wellhead, NU BOP & test casing
- Drill on shoe @ 11:00a.m. 2/7/02, Drill out in 7 7/8" hole & test BOP to 2000#



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mike Hanagan TITLE Agent DATE 5/10/02

Type or print name Mike Hanagan Telephone No. 505-623-1996

(This space for State use)  
 APPROVED BY PAUL F. KAUTZ TITLE ORIGINAL SIGNED BY DATE MAY 17 2002  
 Conditions of approval, if any: PETROLEUM ENGINEER

JCS