

KUKUI Operating Company

DeGas "6" State Com #1

5-1/2" Casing

	# Units	Size	Description	# Feet
Guide Shoe:	1	5-1/2"	Weatherford Model 303 Prem. Grade Float Shoe	1.50
# Jts Casing:	1	5-1/2"	20.0 lbs./ft., P-110, RG 3, LTC, 8rd	42.12
Float Collar:	1	5-1/2"	Weatherford Model 402 prem Grade Float Collar	1.50
# Jts Casing:	307	5-1/2"	20.0 lbs./ft., P-110, RG 3, LTC, 8rd	13,122.63
# Jts Casing:				
# Jts Casing:				
Total casing run.....				13,167.75
Casing cut off..... -				47.75
Casing in hole (BGL).....				13,120.00
Distance RKB to casing head flange..... +				26.00
Casing set at (RKB).....				<u>13,146.00</u>

05/29/02

Cement with Schlumberger (Hobbs).

Lead: 10 bbl CW 100, 620 sx 35:65 Poz Class "H" + 5% DO-44 + 6% DO-20, + .2% DO-46 + .2% D-800, mixed @ 12.8 lbs./gal. & 1.94 cu.ft./sk.

Tail: 550 sx 50:50 Poz Class "H" + 5% DO-44 + 2% DO-20 + .2% D-800, mixed @ 14.4 ppg, 1.31 cu.ft./sk.

Washed out pumps & lines, displace w/290 bbl fresh water. Land plug w/2500 psi. Check floats, held ok. Nipple down BOP, set 5-1/2" casing slips w/200,000 load.

Note: Short Marker Joint: 12,288 - 12,320'
Short Marker Joint : 11,180 - 11,212'

