

DISTRICT I
P.O. Box 1980, Hobbs NM 88240

DISTRICT II

P.O. Drawer DD, Artesia NM 88210

1000 Rio Brazos Rd., Aztec NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION
P.O. Box 2088

WELL API NO.	
30-025-35864	
State	FEE <input checked="" type="checkbox"/>
7. Lease Name or Unit Agreement Name	
Maxwell 26	
8. Well No.	
1	
9. Pool Name or Wildcat	
Wildcat Mississippian	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR TO PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL <input type="checkbox"/> GAS <input type="checkbox"/> WELL <input type="checkbox"/> WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	
2. Name of Operator Yates Petroleum Corporation	
3. Address of Operator 105 South 4th, Artesia, NM 88210	
4. Well Location Unit Letter <u>H</u> : <u>1980</u> Feet From The <u>North</u> Line and <u>880</u> Feet From The <u>East</u> Line Section <u>26</u> Township <u>15S</u> Range <u>34E</u> NMPM <u>Lea</u> COUNTY	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4056' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	
OTHER <input type="checkbox"/>	

SUBSEQUENT REPORT OF:	
REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER <input checked="" type="checkbox"/>	Production Casing

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7-10-02 TD 8-3/4" hole. Ran 5-1/2" 17# and 20# csg set @ 13608'. Float shoe @ 13608'. Float collar @ 13562.79'. Cemented w/150 SCF/bbl nitrified mud + 485 sx Premium Innerfill. Tailed in w/1075 sx Super H w/additives. Rig released 7-13-02.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Stormi Davis

TITLE Regulatory Compliance Tech DATE 7/15/02

TYPE OR PRINT NAME Stormi Davis

TELEPHONE NO 505-748-1471

(This space for State Use)

APPROVED BY _____ TITLE _____

CONDITIONS OF APPROVAL, IF ANY:

ORIGINAL SIGNED BY
PAUL E. KAUTZ
PETROLEUM ENGINEER

DATE JUL 18 2002

RECEIVED
HOBBS
000