

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION
P.O. Box 2088

DISTRICT I
P.O. Box 1980, Hobbs NM 88240

DISTRICT II
P.O. Drawer DD, Artesia NM 88210

1000 Rio Brazos Rd., Aztec NM 87410

WELL APT NO.	
30-025-35864	
State	FEE <input checked="" type="checkbox"/>
7. Lease Name or Unit Agreement Name	
Maxwell 26	
8. Well No.	
1	
9. Pool Name or Wildcat	
Wildcat Mississippian	

SUNDY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL ☐ GAS ☐
WELL ☐ WELL ☒ OTHER ☐

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
105 South 4th, Artesia, NM 88210

4. Well Location
Unit Letter H : 1980 Feet From The North Line and 880 Feet From The East Line
Section 26 Township 15S Range 34E NMPM Lea COUNTY

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
4056' GR


11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER <input type="checkbox"/>		OTHER <u>Spud and Surface Casing</u> <input type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-8-02 Spud 26" conductor hole w/Auger Air @ 10:00 am. Set 40' of 20" conductor pipe.
Notified Sylvia Dickey w/ Hobbs OCD of operations.

5-11-02 Spud 17-1/2" surface hole @ 12:00 am. Notified Sylvia Dickey w/Hobbs OCD of intent to spud and cement 13-3/8" csg. TD 17-1/2" hole @ 406' at 7:45 am. Ran 9 jts 13-3/8" 48# H40 ST&C csg, set @ 406'. Texas Pattern Guide shoe set @ 406'. Insert float set @ 361'. Cemented w/220 sx Premium + 2% CaCl2 + 1/4# /sx Flocele (yld 1.35, wt 14.8). Tailed in w/200 sx Premium + 2% CaCl2 (yld 1.34, wt 14.8). Circulated 72 sx to pit.



I hereby certify that the information above is a true and complete to the best of my knowledge and belief

SIGNATURE Stormi Davis
TYPE OR PRINT NAME Stormi Davis

TITLE Regulatory Compliance Tech DATE 5/15/02

TELEPHONE NO 505-748-1471

(This space for State Use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY

TITLE ORIGINAL SIGNED BY
PAUL F. KAUTZ
PETROLEUM ENGINEER

DATE MAY 22 2002