

State of New Mexico
Energy, Minerals and Natural Resources Department

DISTRICT I

P.O. Box 1980, Hobbs NM 88240

DISTRICT II

P.O. Drawer DD, Artesia NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-35867
5. Indicate Type of Lease	
State <input checked="" type="checkbox"/> FEE <input type="checkbox"/>	
6. State Oil & Gas Lease No.	E-7984
7. Lease Name or Unit Agreement Name	TOWNSTAR ACS STATE
8. Well No.	1
9. Pool Name or Wildcat	WILDCAT MISSISSIPPIAN
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	4041' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL ☐ GAS ☐
WELL ☐ WELL ☒ OTHER ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 South 4th., Artesia, NM 88210

4. Well Location

Unit Letter **L** : **1650** Feet From The **SOUTH** Line and **990** Feet From The **WEST** Line
Section **18** Township **15S** Range **35E** NMPM **LEA** COUNTY

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☒ Spud & surface casing & cement

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4-3-02 - Spudded 24" hole @ 1:00 pm w/ Auger Aire. Set 40' of 20" conductor pipe & redi-mix to surface. Notified Sylvia Dickey w/ Hobbs NMOCD via voice mail of operations.

4-5-02 - MIRU RT - Resume drilling @ 8:00 am MST 4-5-02. TD 17-1/2" hole @ 12:00 pm 4-5-02; circ. TOH to run 13-3/8" casing. Rig up & run 9 jts 13-3/8", 48# H-40 SR, STC = 410.62' @ 406'. Cemented w/ 200 sx Premium Plus w/ 1/4# Flocele, 2% CaCl2 & 220 sx Premium Plus w/ 2% CaCl2. PD @ 5:15 pm 4-5-02. Circ 80 sx to pit. Cut off casing, weld on head, NU BOP. Reduced hole to 12-1/4".
4-6-02 - Drilling formation @ 11:00 am MST - WOC 18-1/4 hrs.

I hereby certify that the information above is a true and complete to the best of my knowledge and belief.

SIGNATURE

Donna Clack

TITLE

Operations Technician

DATE

2/27/02

TYPE OR PRINT NAME

DONNA CLACK

TELEPHONE NO.

505-748-1471

(This space for State Use)

APPROVED BY

TITLE

UNSUBSCRIBED BY
PAUL F. KAUTZ
PETROLEUM ENGINEER

DATE

APR 12 2002

CONDITIONS OF APPROVAL, IF ANY: