

Submit 3 copies to Appropriate District

Office

DISTRICT I

1625 N. French Dr., Hobbs NM 88240

DISTRICT II

1301 W. Grand Avenue, Artesia NM 88210

DISTRICT III

1000 Rio Brizos Rd., Aztec NM 87410

DISTRICT IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, New Mexico 87504-2088

Form C-103

Revised March 25, 1999

WELL API NO.

30-025-36014

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

L-5690

7. Lease Name or Unit Agreement Name

Blue Suede BAT State Com

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

Yates Petroleum Corporation

8. Well No.

1

3. Address of Operator

105 South 4th Str., Artesia, NM 88210

9. Pool Name or Wildcat

Wildcat Mississippian

4. Well Location

Unit Letter E : 1980 feet from the North line and 990 feet from the West line

Section 20 Township 15S Range 35E NMPM County Lea

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3090' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Spud and Surface Casing ☒

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

11-22-02 Spud conductor hole. Set 40' of 20" conductor pipe. Notified Sylvia Dickey w/Hobbs OCD of operations.

11-24-02 Resumed drilling. Notified Hobbs OCD. TD 17-1/2" hole @ 385'. Ran 9 jts 13-3/8" 48# H40 set @ 385'. Cemented w/250 sx Howco Lite Premium Plus. Tailed in w/200 sx Howco Premium Plus + additives. Cement circulated to surface. Reduced hole to 12-1/4" and resumed drilling.

Thereby certify that the information above a true and complete to the best of my knowledge and belief.

SIGNATURE Stormi Davis TITLE Regulatory Compliance Technician DATE 12/2/02

Type or print name Stormi Davis Telephone No. 505-748-1471

(This space for State use)

APPROVED BY PAUL F. KAUTZ TITLE PETROLEUM ENGINEER DATE DEC 10 2002

Conditions of approval, if any: