

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

NM-6863

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Anadarko Federal #1

9. API Well No.

30-025-00872

10. Field and Pool, or Exploratory Area

11. County or Parish, State

Lea Co., N.M.

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Mewbourne Oil Company

3. Address and Telephone No.

P.O. Box 5270 Hobbs, New Mexico 88241

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit Letter: N 660' FSL & 1980' FWL Sec. 27 T18S R32E

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

WILL NOTIFY BLM @ 393-3612 PRIOR TO COMMENCING PLUGGING OPERATION
set CIBP at 3650' ⁺. Spot 15 sx. (35') cement. Circulate hole with mud.
Set 45 sx. plug (100') at 805'. WOC tag top of plug. Set 25 sx. plug at
50' and circulate cement to surface. Cut off wellhead and install P & A
marker. Mud between all plugs.
CEMENT: CLASS 'C' WITH 2% CaC (2) MIXED w/ 6.3 GALS. WATER/SACK.
MUD BETWEEN CEMENT PLUGS: NOT LESS THAN 9.0 PPg.

14. I hereby certify that the foregoing is true and correct

Signed

Title District Supt.

Date 06/06/91

(This space for Federal or State office use)

Approved by

Title

Date 6-10-91

Conditions of approval, if any:

RECEIVED

MUN 1 199

MOORE