

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> WIW		5. LEASE DESIGNATION AND SERIAL NO. <u>LC 069497</u>	
2. NAME OF OPERATOR <u>Yates Petroleum Corporation</u>		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR <u>207 S. 4th Street; Artesia, N.M. 88210</u>		7. UNIT AGREEMENT NAME <u>Young Unit</u>	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface <u>Sec 29-T18S-R32E, 330' FNL, 1650' FWL</u>		8. FARM OR LEASE NAME <u>Young Unit</u>	
14. PERMIT NO.		9. WELL NO. <u>30</u>	
15. ELEVATIONS (Show whether DF, RT, GR, etc.)		10. FIELD AND POOL, OR WILDCAT <u>Young Queen</u>	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <u>Sec 29-T18S-R32E</u>	
		12. COUNTY OR PARISH <u>Lea</u>	
		13. STATE <u>N.M.</u>	

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Return well to injection

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10/6/84 - 10/18/84

Pulled Tbg and pkr, RIH with Bit and scraper, CO to 4049'. Sqz. Penrose perforations 3938-3956' with 75 sxs Class "C" 5# Salt. Isolated csg. leaks 2910-2943' and 530-545'. Cmt (via 4½" csg.) 530-545' with 110 sxs Class "C" 2% CaCl₂ to surface. Sqz. 115 sxs Class "C" 2% CaCl₂ between 4½" and 8-5/8" casg. Drilled cmt. plug 452-538'. Test csg. surface to 2810' with 1000#, OK. Sqz. csg. leak 2910-2943' with 50 sxs Class "C" 2% CaCl₂ 5# salt to 1500#. Reverse out 5 sxs. Drilled out retainer and cement 2812-2943'. TIH with 4½" packer on 120 joints 2-3/8" plastic coated tbg, set @ 3642'. Pressure test annulus to 500# with chart and held for 15 minutes. Returned well to injection through Queen perforations 3711-3749'.

RECEIVED

NOV 14 1984

18. I hereby certify that the foregoing is true and correct

SIGNED

David Ramsey

TITLE

Petroleum Engineer

DATE

11/2/84

(This space for Federal or State office use)

APPROVED BY

GWQ

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

NOV 14 1984

*See Instructions on Reverse Side

Carlsbad,

NEW MEXICO