Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE (Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.
NM-01235-D

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL [X] GAS WELL [ ] OTHER

7. UNIT AGREEMENT NAME

2. NAME OF OPERATOR
PAN AMERICAN PETROLEUM CORPORATION

8. FARM OR LEASE NAME
BONDURANT Fed

3. ADDRESS OF OPERATOR
BOX 68, HOBBS, N. M. 88240

9. WELL NO.
1

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface
2310' FSL & 330' FEL Sec 13 (UNIT I, NE/4 SE/4)

10. FIELD AND POOL, OR WILDCAT
TONTO YATES SEVEN RIVERS, WEST

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
13-19-32 NMPM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3643' R.D.B.

12. COUNTY OR PARISH
LEA

13. STATE
N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF	[ ]	PULL OR ALTER CASING	[ ]	WATER SHUT-OFF	[ ]	REPAIRING WELL	[X]
FRACTURE TREAT	[ ]	MULTIPLE COMPLETE	[ ]	FRACTURE TREATMENT	[ ]	ALTERING CASING	[ ]
SHOOT OR ACIDIZE	[ ]	ABANDON*	[ ]	SHOOTING OR ACIDIZING	[ ]	ABANDONMENT*	[ ]
REPAIR WELL	[ ]	CHANGE PLANS	[ ]				
(Other)			[ ]	(Other)			

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

In accordance with Form 9-331 submitted 11-18-68, remedial work performed as follows:

Squeezed perforations 3247-50' w/ 203 Sx Cement.

Perforated 3236-40 w/2JSPF and acidized w/ 250 gal 15%. Evaluated. Workover unsuccessful & Well Shut In. for further evaluations and possible deepening.

Prior - Pmp 8 BO x 500 BW 24 hrs.
after - Flow 0 BO x 30 BW 24 hrs. 628 MCFGPD, TDF 395, CPC-610.

TD-3253'
PBD-3243'
4½" CSA 3282'

OC - 11-18-68
SI - 12-6-68

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE AREA SUPERINTENDENT DATE MAR 7 1969

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

APPROVED
MAR [illegible]
J. A. GORDON
ACTING DISTRICT ENGINEER

OCC-4-USGS-H
1-NSW
1-SUSP
1-12RV
1-CONOCO

*See Instructions on Reverse Side