

NMOCC

Form 9-331a
(March 1942)

Budget Bureau No. 42-R358.
Approval expires 11-30-46.

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces

Lease No. 030850

Unit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Midland, Texas, March 27, 1945

C. F. Knight

Well No. 1 is located 660 ft. from N line and 660 ft. from E line of sec. 13

NE 1/4 Sec. 13

(1/4 Sec. and Sec. No.)

19-S

(Twp.)

32-E

(Range)

N.M.P.M.

(Meridian)

East Lusk

(Field)

Lea

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 3646 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

This well has been drilled to total depth of 4243' without encountering oil or gas production, and has been abandoned, plugging as follows. A cement plug of 30 sacks was spotted in the bottom of the hole from 4243' to 4130'. Hole was filled with heavy mud and the following cement plugs were spotted: 30 sacks, 3550-3450'; 25 sacks, 3320-3260'; 20 sacks, 2900-2830' (at base of salt); and 20 sacks, 1429-1369' (at top of salt and in bottom of 8-5/8" casing). The 8-5/8" casing was parted and pulled at 760' and a 20-sack cement plug spotted from 785' to 725'. A plug of 20 sacks of cement was spotted in the bottom of the 13-3/8" casing from 320' to 280' and the required 4" pipe marker was cemented in the top of the hole with 10 sacks of cement. All above work was completed on 12-23-44, and location is now cleaned up and ready for inspection.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company The Texas Company

Address Box 1270

Midland, Texas

By

L. F. Shupert

Title District Superintendent