



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office

Lease No.

Unit

RECEIVED
JUN 12 1963

VARIOUS DRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	X	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Plains Unit

June 5, 1963

Well No. 1 is located 660 ft. from N line and 660 ft. from E line of sec. 27
NW/4 - NW/4, Sec. 27 T-19-S, R-32-E NMPN
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Laek Morrow Lee New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3607 ft. RID

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Pursuant to telephone approval of June 4, 1963, between Messrs. A. R. Brown and J. W. Meek, the following remedial work is proposed.
Perforate Additional Morrow intervals 12,670-78, 12,702-06, 12,747-50
12,890-94, 12,902-11, 12,936-46 with 2 SPT. Spot 500 gal acid and acid-free with 25,000 gal gelled acid containing 1/2" sand/gal. Soak in and test. Restore to production.

(TD 13,160', PBD 13,082', Perfs. 13,004'-13,010')

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pan American Petroleum CorporationAddress Post Office Box 68Hobbs, New MexicoOriginal Signed by:
W. E. STALEY

By

Title Area Superintendent

