

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name Corbin Abo SWDS
9. Well No. G-31
10. Field and Pool, or Wildcat Corbin
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Salt Water Disposal
2. Name of Operator AGUA, INC
3. Address of Operator P.O. Box 1978 Hobbs, N.M. 88240
4. Location of Well UNIT LETTER <u>G</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>31</u> TOWNSHIP <u>17S</u> RANGE <u>33E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3983' GL

18. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input checked="" type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1105.

Pursuant to Order No. R3564:

1. Drillout Cal-seal & gravel plug from 4925 to 4956'
2. Circulate down to cmt. plug @ 5510'
3. Drill cmt. plug from 5510 to 5600'
4. Circulate down to 6375'
5. Spot 100 sk. cmt. plug @ 6375'
6. Treat perforated intervals 4530-58', 4598-4628' and open hole interval 4894 - 6375' with 10,000 gals. 15% HCl acid.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>W.G. Abbott</u>	TITLE <u>Manager</u>	DATE <u>Oct. 3, 1975</u>
APPROVED BY <u>John Runyan</u> Geologist	TITLE _____	DATE <u>OCT 7 1975</u>
CONDITIONS OF APPROVAL, IF ANY:		