

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☐ Conversion to wtr. inj
2. NAME OF OPERATOR
Phillips Petroleum Company
3. ADDRESS OF OPERATOR
Rm, 401, 4001 Penbrook St., Odessa, Tx 79762
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1650'FNL & 1650'FWL
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF ☐ ☐
FRACTURE TREAT ☐ ☐
SHOOT OR ACIDIZE ☐ ☐
REPAIR WELL ☐ ☐
PULL OR ALTER CASING ☐ ☐
MULTIPLE COMPLETE ☐ ☐
CHANGE ZONES ☐ ☐
ABANDON* ☐ ☐
(other) Deepened well & set 4-1/2' Csg

5. LEASE
NM801
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
- - -
7. UNIT AGREEMENT NAME
- - -
8. FARM OR LEASE NAME
Wyatt A Federal
9. WELL NO.
4
10. FIELD OR WILDCAT NAME
Corbin Queen
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 33, T-17-S, R-33-E
12. COUNTY OR PARISH 13. STATE
Lea New Mexico
14. API NO.
30-025-01367
15. ELEVATIONS (SHOW DF, KDB, AND WD)
NR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-18-84: MI & RU workover rig.
12-19-84: NU BOP. Tagged cmt @2502', drld cmt to 2533'
12-20 thru
12-24-84: Drld cmt to 2850'. Washed and reamed hole & tagged sand @3590'. Tried to latch onto RBP & POOH.
12-25-84: SD for Christmas.
12-26 thru
12-27-84: Tagged RBP @3658', unsuccessfully attempted to latch onto RBP and pull out of hole. WIH w/wash pipe, tagged RBP & pushed to 3673'.
12-28-84: WIH w/impression block, junk on top of RBP.
12-29 thru
1-04-85: Milled and cleaned out hole.

SEE REVERSE SIDE

Subsurface Safety Valve: Manu. and Type n/a Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. J. Mueller TITLE DATE February 25, 1985

(This space for Federal or State office use)

APPROVED BY TITLE DATE
CONDITIONS OF APPROVAL, IF ANY:

1-10

thru

RECEIVED
MAR 7 1985

1-20-85: Drilled 3744' to 4750'. TD'd 6 1/4" hole @ 1:30 am.

1-21-85: Ran CDL-LDT-GR/cal, TD to 3680'; DDL-RXO-Cal, TD-3680'

Began casing.

1-22-85: 11.6# N-80 LTRC casing at 4750'. Cmt'd w/300 sx TLM w/10% DD, 10%

salt 1/4#/sx floreal, 3#/sx gilsonite followed w/150 sx Class C w/6# /sx

circ 25 sx.

1-23 thru

2-22-85 Evaluating logs and preparing procedure to convert to injection.