


JUL 1 1960

E. W. STANLEY  
DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office \_\_\_\_\_

Lease No. LC-060967

Unit \_\_\_\_\_

RECEIVED

JUL 11 1960

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	X
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 8, 1960

Well No. 1 is located 1980 ft. from [N] line and 812 ft. from [E] line of sec. 33

SE NE 33  
(¼ Sec. and Sec. No.)17S  
(Twp.)33E  
(Range)

(Meridian)

Undesignated  
(Field)Lea  
(County or Subdivision)New Mexico  
(State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

BJ Co. cemented 8-5/8" 24# J55 casing at 4589' w/ 910 sx. Incore SR 40%  
Diocel D followed by 150 sx regular cement. Cement circulated to surface.  
Complete 6:30 p.m. 7-4-60. WOC 36 hours. Tested casing with 1500# pressure  
for 30 minutes, no pressure loss.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Phillips Petroleum Company

Address Box 2105

Hobbs, New Mexico

By [Signature]  
Title District Chief Clerk