(Feb. 1951)							
i							
	<b></b>		<b></b>				

Form 9-831 a

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land	Office	
Lease	No. LC060967	
Unit .	Zilliams	

NOTICE OF IN					
	TENTION TO DRILL		SUBSEQUENT RE	PORT OF WATER SHUT-OFF	- X
NOTICE OF IN	TENTION TO CHANGE PLANS	i		PORT OF SHOOTING OR AC	
NOTICE OF IN	TENTION TO TEST WATER SHU	T-OFF	FI .	ORT OF ALTERING CASING	
l	TENTION TO RE-DRILL OR REP	1	SUBSEQUENT REI	ORT OF RE-DRILLING OR	REPAIR
	TENTION TO SHOOT OR ACIDIZ	+	11:	ORT OF ABANDONMENT	Į.
1	TENTION TO PULL OR ALTER OF TENTION TO ABANDON WELL.		SUPPLEMENTARY	WELL HISTORY	
	TENTION TO ABANDON WELL	***************************************			
	(INDICATE ABO)	E BY CHECK MARK	NATURE OF REPORT, NO	TICE, OR OTHER DATA)	
			Cetob	er 18, 1960	, 19_
illians Vell No.	is located 23	110 ft. from	N line and 19	81. ft from (E)	line of sea 33
	4 Section 33		33-8	TC. Hom W	inte of sec.
(¼ Sec. Und es i gn	and Sec. No.)		(Range)	(Meridian)	
	Field)	Lea County of	r Subdivision)	(State or T	
itate names of a					
SH & K D  Cemented  VCC 18 h	rilling Company : 13-3/8" (27 & 48 ours. Tested cas	) casing	at 330' with	350 sacks cemer	nt. Flug to 3 sure less. Ce
SH & K D Cemented V(C 18 h	13-3/8" (27 & 48 ours. Tested cas	) casing	at 330' with	350 sacks cemer	nt. Flug to 3 sure less. Ce
SH & K D  Comented  V(C 18 h	13-3/8" (27 & 48 ours. Tested cas	) casing	at 330' with	350 sacks cemer	nt. Flug to 3 sure less. Ce
SH & K D Cemented V(C 18 h	13-3/8" (27 & 48 ours. Tested cas	) casing	at 330' with	350 sacks cemer	nt. Flug to 3 sure less. Ce
SH & K D  Comented  CC 18 h  circulat	13-3/8" (27 & 48 ours. Tested case of to surface.	ing with 50	at 330° with 00% for 30 mi	350 sacks cemer nutes, no press	sure loss. Ce
SH & K D  Comented  KC 18 h  circulat  Tunderstand	13-3/8" (27 & A8 ours. Tested case of to surface.	ing with 50	at 330° with 00% for 30 mi	350 sacks cemer nutes, no press	sure loss. Ce
Cemented WC 18 h circulat	13-3/8" (27 & 48 ours. Tested case of to surface.	ing with 50	at 330° with 00% for 30 mi	350 sacks cemer nutes, no press	sure loss. Ce
SH & K D  Comented  KC 18 h  circulat  Tunderstand	13-3/8" (27 & A8 ours. Tested case of to surface.	casing (ing with 50	at 330° with 00% for 30 mi	350 sacks cemer nutes, no press	s may be commenced.