

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Form Approved.  
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other ☒ S W D

2. NAME OF OPERATOR

M & W of Lovington, Inc.

3. ADDRESS OF OPERATOR

Box 922, Lovington, NM 88260

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 2310' FSL & 330' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: 4702'

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☒  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

RELEASE

COCKBURN Federal NM 04242

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

COCKBURN FED. NM 04242

8. FARM OR LEASE NAME

9. WELL NO.

8

10. FIELD OR WILDCAT NAME

CORBIN QUEEN

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

S-34, T-17S, R-33 ENMPM

12. COUNTY OR PARISH

LEA

13. STATE

NEW MEXICO

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
DF 4122

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Rig unit up & swedge out 5-1/2" csg. @ 500' from surface with 3-1/2" swedge.
2. Run 2" tbg. to 4300' & tag spot 50 sks of frac sand over perf & let fall 24hrs.
3. Tag sand & spot 50' cmt plug & shut down.
4. Tag bottom plug.
5. Fill hole with drilling mud.
6. Spot 50' cmt plug @ 2600' (base of salt).
7. Perf csg @ 1630' & spot 50' cmt plug.
8. Perf csg @ 172' & spot 100' plug in & out of 8-5/8 csg 50' in & 50' out of 8-5/8 csg. [TAG] (SJS)

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

*John W. Wilson*

TITLE

President

DATE

1-17-90

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

1-26-90

CONDITIONS OF APPROVAL, IF ANY: