X

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

| Land Office | Las Cruces |
|-------------|------------|
| Lease No. | 060967 |
| Unit | y |
| Wyatt-P | hillips #7 |

| NOTICE OF INTENTION TO DRILL | X | SUBSEQUENT REPORT OF WATER SHUT-OFF | |
|--|------------------------------|---|-------------------|
| NOTICE OF INTENTION TO CHANGE PLANS | | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING. | |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | i | SUBSEQUENT REPORT OF ALTERING CASING | |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | 1 | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR | |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | | SUBSEQUENT REPORT OF ABANDONMENT. | |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | | SUPPLEMENTARY WELL HISTORY | |
| NOTICE OF INTENTION TO ABANDON WELL | | | |
| (INDICATE ABOVE BY CHECK MA | ARK NAT | TURE OF REPORT, NOTICE, OR OTHER DATA) | |
| | | Peb. 11. , 19 | 54 |
| Vijatt - Phillips | (| (NT) (#EV) | |
| ell No. 7 is located 2310 ft. fro | om { | $\begin{bmatrix} N \\ S \end{bmatrix}$ line and 1650 ft. from $\begin{bmatrix} 127 \\ W \end{bmatrix}$ line of sec. 34 | |
| | | | |
| (1/4 Sec. and Sec. No.) (Twp.) | (Pai | ine) (Meridian) i. Hex. ladivision) (State or Territory) | |
| Corbin = axtension | Le | (State or Torritory) | |
| <u> </u> | all other | weights, and lengths of proposed casings; indicate mudding jobs, cer important proposed work) the red sand, expected at approximate | |
| We propose to drill this well to 3900 feet. The well will be topo of 8 5/8" surface casing will be | test | the red sand, expected at approximate n with rotery tools and approx. 1400 f From there the well will be complete | ly oet |
| We propose to drill this well to 3900 feat. The well will be topo of 8 5/8" surface casing will be | test | the red sand, expected at approximate n with rotery tools and approx. 1400 f From there the well will be complete | ly oet |
| We propose to drill this well to 3900 feat. The well will be topo of 8 5/8" surface casing will be | test | the red sand, expected at approximate n with rotery tools and approx. 1400 f From there the well will be complete | ly oet |
| We propose to drill this well to 3900 feat. The well will be topo of 8 5/8" surface casing will be | test | the red sand, expected at approximate n with rotery tools and approx. 1400 f From there the well will be complete | ely 'eet ed |
| We propose to drill this well to 3900 feat. The well will be topp of 8 5/8" surface casing will be with cable tools and 7" casing wi | test ed i run. | the red sand, expected at approximate n with rotary tools and approx. 1400 f From there the well will be complete a run to the top of the red sand. | ly look d |
| We propose to drill this well to 3900 feat. The well will be toom of 8 5/8" surface casing will be with cable tools and 7" casing wi | test ed 1 run. 11 b | the red sand, expected at approximate r with rotery tools and approx. 1400 f From there the well will be complete a run to the top of the red sand. | ly look d |
| We propose to drill this well to 3900 feat. The well will be topp of 8 5/8" surface casing will be with cable tools and 7" casing will be will be with cable tools and 7" casing will be will | test ed i run. | the red sand, expected at approximate with rotary tools and approx. 1400 f From there the well will be complete a run to the top of the red sand. | ly lees d |
| We propose to drill this well to 3900 feat. The well will be toom of 8 5/8" surface casing will be with cable tools and 7" casing wi | test ed i run. 11 b | the red sand, expected at approximate with rotary tools and approx. 1400 f From there the well will be complete a run to the top of the red sand. | ly lees d |