## NEW MEXICO OIL CONSERVATION COMMISSION

### Santa Fe, New Mexico

# MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

#### Indicate Nature of Notice by Checking Below

Notice of Intention to Change Plans	NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	Notice of Intention to Plug Back		Notice of Intention to Set Liner	<u> </u>
Notice of Intention to Squeeze	Notice of Intention to Acidize		Notice of Intention to Shoot (Nitro)	
Notice of Intention to Gun Perforate	Notice of Intention (Other)	x	Notice of Intention (Other)	

OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO

Abilene, Toxas

5-25-61 (Data)

Gentlemen:

### FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

We plan to move rotary rig on this well which was previously temporarily abandoned. We plan to run a bit and drill pipe in the hole and drill the plug out from 4000' to 4150'. The bit and drill pipe will then be run on down the hole to a depth of 6900'. The hole will be circulated with mud and properly conditioned. Following this we will spot a 20 sack cement plug at 6900'. After this we will spot a 20 sack cement plug at 6300'. Following this we will spot a 100 sack regular neat cement plug from a depth of 5310' back to a depth of 5050'. Following this we will spot a 100 sack regular neat cement plug from 4720' to a depth of 4450'. This plug will seal off the top and bettom portions of the porosity in the Grayburg and San Andres. Following this we will spot a 100 sack cement plug from 4300' back to 4050'. Following this the hole will be conditioned with mud and 5 1/2" O. D. casing will be set at 4050' and sufficient cement will be used to bring the top of the cement on the outside of the 5 1/2" casing up into the 8 5/8" O. D. casing which has been previously set and cemented at 3100'.

Approved	McMahon, Wiley & Lowe
Except as follows:	By Vi Annue
	Position Agent
Approved	Send Communications regarding well to:
OIL CONSERVATION COMMISSION	
By Leslie N. Clements	Name. McMahon Wiley & Lowe
Title	Addres 814 Citizens Nat'l Bak., Abilene, Texa