

DUPLICATE

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

RECEIVED  
OCT 18 1946  
REGISTRY

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ~~three~~ <sup>three</sup> days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

Midland, Texas.

8/9/46

Place

Date

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

C. J. CHANCELLOR Oil State Well No. 1 in the

Company or Operator

Lease

City of SEA of Sec. 27, T. 17 S., R. 33E, N. M. P. M.,  
wildcat Field, Lea County.

The dates of this work were as follows: August 5 to 9th 1946

Notice of intention to do the work was (was not) submitted on Form C-102 on August 4, 1946 19

and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Hole was dry at 4702'. Bailed after standing over night about 5 gallons of oil and 1 bailer of water. Halliburton filled hole with mud to bottom of salt, set bridge and cemented with 10 sacks of cement, filled hole to 1600' with mud, set bridge and cemented with 10 sacks filled hole with mud to bottom of 8 5/8" pipe at 1400'. Shot pipe off at 1000'. Recovered 1000' of 8 5/8" pipe filled hole with mud to 300' set bridge and cemented with 15 sacks. Filled hole to top and cemented in 1/2 joint of 8".

Witnessed by

C. J. Chancellor

Name

Company

Title

Owner

Subscribed and sworn before me this 9th

I hereby swear or affirm that the information given above is true and correct.

day of August, 19 46

Name

Position Owner

Representing

Company or Operator

My commission expires June 1, 1947

Address Box 15 Midland, Texas.

Remarks:

APPROVED

Date OCT 18 1946

Roy Yarbrough  
Oil & Gas Inspector