

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 1300 feet, and from feet to feet.
 Cable tools were used from 1300 feet to 5051 feet, and from feet to feet.

PRODUCTION

Put to Producing. Dry hole, 19.

OIL WELL: The production during the first 24 hours was. barrels of liquid of which % was
 was oil; % was emulsion; % water; and % was sediment. A.P.I.
 Gravity.

GAS WELL: The production during the first 24 hours was. M.C.F. plus. barrels of
 liquid Hydrocarbon. Shut in Pressure. lbs.

Length of Time Shut in.

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico			Northwestern New Mexico		
T. Anhy.			T. Devonian.		T. Ojo Alamo.
T. Salt.			T. Silurian.		T. Kirtland-Fruitland.
B. Salt.			T. Montoya.		T. Farmington.
T. Yates.			T. Simpson.		T. Pictured Cliffs.
T. 7 Rivers.			T. McKee.		T. Menefee.
T. Queen.			T. Ellenburger.		T. Point Lookout.
T. Grayburg.			T. Gr. Wash.		T. Mancos.
T. San Andres.			T. Granite.		T. Dakota.
T. Glorieta.			T.		T. Morrison.
T. Drinkard.			T.		T. Penn.
T. Tubbs.			T.		T.
T. Abo.			T.		T.
T. Penn.			T.		T.
T. Miss.			T.		T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	230	230	Red bed and sand	3775	3835	60	Anhydrite and broken red sand
230	350	120	Red sand	3835	3875	40	Anhydrite & broken red sand
350	390	40	Red bed	3875	4110	235	Anhydrite
390	410	20	Gray sand	4110	4140	30	Sand
410	490	80	Shale (red) & gray sand	4140	4173	33	Anhydrite
490	555	65	Red bed; shells	4173	4180	7	Lime
555	1135	580	Red bed	4180	4330	150	Anhydrite & lime shells
1135	1220	85	Red bed & gyp	4330	4362	32	Broken lime
1220	1410	190	Red rock	4362	4370	8	Pink lime
1410	1423	13	Red bed	4370	4488	118	Lime
1423	1550	127	Anhydrite	4488	4500	12	Brown sand
1550	1570	20	Salt & anhydrite	4500	4520	20	Sand & anhydrite
1570	1620	50	Anhydrite	4520	4532	12	Pink lime
1620	1630	10	Salt	4532	4535	3	Gray lime
1630	1675	45	Salt, anhydrite & red rock	4535	4570	35	Lime
1675	2520	845	Salt	4570	4575	5	Sand
2520	2560	40	Salt & anhydrite	4575	4600	25	Bentonite
2560	2685	125	Salt	4600	4615	15	Gray sand & anhydrite
2685	3060	375	Anhydrite. show of oil	4615	4645	30	Lime & anhydrite
3060	3085	25	Broken anhydrite	4645	4650	5	Gray lime
3085	3205	120	Anhydrite	4650	4885	235	Lime
3205	3230	25	Broken anhydrite	4885	4930	45	Lime & sand
3230	3305	75	Sandy anhydrite	4930	4940	10	Lime
3305	3710	405	Anhydrite	4940	5000	60	Lime & Sand
3710	3775	65	" & gray sand	5000	5051	51	Lime

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

July 9, 1954

Company or Operator. GEORGE WILLIAMS
 Name. *George Williams*
 Address. 207 West Avenue B, Lovington, N. M.
 Position or Title. Agent