

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☒ WIW

MAR 10 1981

2. NAME OF OPERATOR

Mobil Producing TX. & N.M. INC. U.S. GEOLOGICAL SURVEY

3. ADDRESS OF OPERATOR

9 Greenway Pl., Suite 2700, Houston, TX 77046

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: Unit Letter M, 660 FSL & 990 FWL

AT TOP PROD. INTERVAL: Same as surface

AT TOTAL DEPTH: Same as surface

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐(other) ☐☐☐☐☐☐☐☐☐☒

5. LEASE

NM-04591

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

E. K. Queen Unit Tr. 6

9. WELL NO.

4

10. FIELD OR WILDCAT NAME

E. K. Yates 7 Rivers Queen

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 13, T18S, R33E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3918 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2-11-81 MIRU, instl BOP

2-12-81 POH & LD 139 jts 2-3/8 CL tbq=4320' & GUIB pkr, GIH w/HOWCO 5 1/2" cmt ret & 2-3/8 tbq work string & set @ 3315, sqz cmt Yates perfs 3527-37 & Queen OHZ 4329-55 w/150sx Class C Neat cmt, Displ 5 1/2 cst to 9.5#/gal. MLF, pull & LD 9 jts 2-3/8 tbq

2-15-81 POH w/95 jts 5 1/2" 15.5# csg rec 3036' HOWCO set 50 sxs C neat 3112-2825 pull tbq to 1712, cmt 8-5/8 shoe w/50 sxs C 1712-1500 POH LD 2-3/8

2-16-81 Pull 19 jts 8-5/8 24# csg=572'

2-17-81 GIH w/8-5/8 CIBP & set @ 1616, spot 50 sxs Class C cmt on top of CIBP & spot 50 sx Class C cmt @ 635, displ csg to 9.5#/gal MLF, SPOT 100 sxs Class C neat cmt @ 350' & 25 sxs Class C cmt @ 30' to surf, weld on plate & P&A marker

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Diane K. Black

TITLE Authorized Agent

DATE 3-2-81

APPROVED

(This space for Federal or State office use)

APPROVED BY

(Sig. Sgd.) PETER W. CHESTNUT

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY

NOV 5 1982

FOR

JAMES A. GILLHAM
DISTRICT SUPERVISOR

*See Instructions on Reverse Side