

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYForm Approved
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen a well, or to alter a well, or to alter a reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☒ WIW

2. NAME OF OPERATOR

Mobil Producing TX. & N.M. Inc.

3. ADDRESS OF OPERATOR

9 Greenway Plaza, Suite 2700, Houston, TX 77046

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: Unit Letter M, 660' FSL & 990' FWL

AT TOP PROD. INTERVAL: Same as surface

AT TOTAL DEPTH: Same as surface

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☒

(other)

SUBSEQUENT REPORT OF:

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1) MIRU, pull 2-3/8" cement lined tubing and packer

2) Run 5 1/2" cement retainer on working string, set at 3300'

3) Squeeze 150sx Class C neat cement through retainer

4) Displace hole with 80 bbls 9.5 ppg mud laden fluid to surface

5) Cut casing with jet cutter, pull all free 5 1/2" casing

6) Spot 50sx Class C neat cement from 100' below cut to 150' above cut

7) Spot 50sx Class C neat cement 1700' to 1500'

8) Cut casing with jet cutter, pull all free 8-5/8" casing

9) Spot 50sx Class C neat cement from 50' below cut to 80' above cut

10) Spot 100sx Class C neat cement from 350' to 170'

11) Spot 15sx Class C neat cement from 20' to surface

12) Remove wellhead, weld plate, fill cellar, set P&A marker, clean location

NOTE: Procedure verbally approved by Karen Sales, USGS-Roswell. Contact her at
Subsurface Safety Valve: Manu. and Type 505-622-1332 24 hrs prior to P&A. Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Diane K Black TITLE Authorized Agent DATE December 15, 1980

(This space for Federal or State office use)

APPROVED BY (Orig. Sgd.) PETER W. CHESTER TITLE MINING DISTRICT ENGINEER DATE DEC 21 1980
CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well sit-conditioned for final inspection looking to approval of the abandonment.