

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

6. LEASE DESIGNATION AND SERIAL NO.

LC 064944

8. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

New Mexico Fed. H

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

E. K. Queen

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

27-18-33

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Aztec Oil and Gas Company

3. ADDRESS OF OPERATOR

Box 2010, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface1980' from South and 660' from West
Section 27, Township 18, Range 33.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☒CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Spot a 25 sx. cement plug at TD to cover existing perforations.
2. Load hole with mud laden fluid.
3. Shoot and recover approximately 1500' of 5-1/2" casing.
4. Spot a 35 sx. cement plug at stub of casing.
5. Spot a 50 sx. cement plug in and out of base of 8-5/8" casing set at 216'.
6. Spot a 10 sx. cement top hole plug and erect a regulation marker.

18. I hereby certify that the foregoing is true and correct

SIGNED

Arthur R. Brown

TITLE

Agent

APPROVED

DATE

5/16/73

(This space for Federal or State office use)

APPROVED BY

TITLE

MAY 21 1973

ARTHUR R. BROWN
DISTRICT ENGINEER

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side