

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions
reverse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)HOBBS OFFICE 0665
Nov 3 8 21 AM '63

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	5. LEASE DESIGNATION AND SERIAL NO. 20-42-117
2. NAME OF OPERATOR Pan American Petroleum Corporation	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR Box 68 - Hobbs, New Mexico - 88240	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2082' FWL X 1980' FWL Sec. 3 (Unit F, SE/4, NW/4)	8. FARM OR LEASE NAME SEA Mark Melan 451-
14. PERMIT NO.	9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3748' RDB	10. FIELD AND POOL, OR WILDCAT Undesignated Bone Springs
	11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA 3-19-30 NEEN
	12. COUNTY OR PARISH Lea
	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☒(Other) Recompletion Oper. ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

In accordance with Form 9-331a dated October 6, 1963, Pennsylvania abandonment and Bone Springs recompletion work performed was as follows:

"Squeezed Morrow (Penn) perforations 13,200'-44' with 100 sx cement. 40 sx in formation and 60 sx on top of Baker Model "DF" Packer. Set at 13,088'. Set bridge plug at 10,500'. Perforated 1" casing at 10,175'. Squeezed behind casing with 138 sx. Drilled out to 10,345'. (PED). Perforated Bone Springs interval 10,314'-28' with 2 SFF. Acidized with 9000 gallons. Evaluated.

On P.T. well pumped 38 EO x 25 BW in 24 hours. GOR 176. GGR 33.2°.

OG 10-16-63, Comp. 11-21-63

APPROVED

NOV 29 1963

E. G. HUBBLE
ACTING DISTRICT ENGINEER

18. I hereby certify that the foregoing is true and correct

Original Signed by:
SIGNED V. E. STALEY

TITLE Area Superintendent

DATE 11-27-63

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.