

NEW MEXICO OIL CONSERVATION COMMISSION

Santa, Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	X
NOTICE OF INTENTION TO DEEPEN WELL		DUPLICATE	

Hobbs, New Mexico

March 22, 1939

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.Note- Will notify Oil Conservation Commission
by phone when work is started.

Gentlemen:

Following is a notice of intention to do certain work as described below at the

Repollo Oil Company State # 197 Well No. 2 in SE/4
Company or Operator Lease

of Sec. 6, T. 17S, R. 34E, N. M. P. M., Vacuum Field,
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

Total Depth 5015' - Reason for plugging- Very small stain of oil 280' of Salt Water in hole encountered from 5009 to 5015'. Propose to cement from 5015 to well up into 7"OD Casing which is set @ 4545'. After cement sets will fill 7"OD Casing with heavy mud to approximately 2500' from top and then knock 7"OD casing off and then fill 7"OD casing with heavy mud to approximately 500' from top of hole and pull 7"OD casing adding mud as necessary to keep top of mud within 500' of top of hole. Then knock off 9 5/8"OD casing at approximately 500' from top of hole which is set @ 1574'. After knocking off 9 5/8"OD casing will set cement plug at point knocked off, allow to set and fill 9 5/8"OD casing with heavy mud to bottom of cellar and then pull the 9 5/8"OD casing, keeping casing full of mud while pulling. Allow mud to settle, run cement plug in bottom of cellar cementing a piece of 4" pipe of sufficient length, in the bottom of cellar to extend 4' above the ground level, as the regulation "MARKER". After "Marker" is cemented will fill cellar level with surface.

Approved MAR 24 1939, 19
except as follows:

Repollo Oil Company
Company or Operator

By

Position

Dist. Supt.

Send communications regarding well

Name

L. Surrent

Address

Hobbs, N.M.

OIL CONSERVATION COMMISSION,

By

Title OIL & GAS INSPECTOR

