

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- WIW		5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
2. Name of Operator Mobil Oil Corporation		5. State Oil & Gas Lease No. B-1520
3. Address of Operator Box 633, Midland, Texas 79701		7. Unit Agreement Name
4. Location of Well UNIT LETTER I 1980 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 11 TOWNSHIP 17-S RANGE 34-E		8. Farm or Lease Name Bridges State'
		9. Well No. 74
		10. Field and Pool, or Wildcat Vac-G-SA
15. Elevation (Show whether DF, RT, GR, etc.) 4036 GR		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☒

OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4770 TD. P & LD 115 jts 2-3/8 Buttress PC tbq, tbq parted @ 3634, ran 4-11/16 OS w/ 2-3/8 grapples on 2-7/8 work tbq, caught fish @ 3634, attempted to rel pkr or break safety jt w/ no success. Homco ran string shot to 4400 backed off 2-3/8 PC tbq, POH, ran 4-5/8" overshot w/2-19/32" grapples on B sub, jars, 4 3-1/2" DC's accelerator sub & 2-7/8 tbq to 4400, caught fish jarred 15 min, jarred loose. POH, rec all fish, ran Howco Easy drill ret & set @ 4560, Howco sqz SA perfs 4611-4639 OA w/100x Class H cmt, Max psi 1500, displ hole 9.5# mud laden fluid, pull 20 stands, LD tbq to 1831, spot 25xClass H cmt 1831-1540, finish LD tbq, remove BOP, cut wellhead off, spot 10x plug @ surf, instl P&A marker, job compl 3 pm 12/28/74, P&A 12/28/74.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine O. Tucker

TITLE Authorized Agent

DATE 1-3-75

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: