

STATE BRIDGES NO. 74 Continued

CORE RECORD Continued

No.	From	To	Req.	Description
5	4712	4750	38'	4712-4716, dolo, gray buff oolitic, poorly cemented, good odor, stain & fluorescence, 4716-4719, dolo, finely crystalline, gray 5% scattered inner crystals & vuggy pore, good stain & fluor, 4719-4722, dolo, finely crystalline buff, no shows, 4722-4730 $\frac{1}{2}$, dolo, finely crystalline tan, 5% inner crystals, porosity & vuggy pore, good stain & fluor, 4730 $\frac{1}{2}$ -4746, dolo, finely crystalline buff to brown, no shows, 4746-4750, dolo, finely crystalline buff w/scattered vuggy pore, dead oil stain & odor.
6	4750-	4770	20'	4750-4751, dolo, finely crystalline tan, 4751-4752 $\frac{1}{2}$, dolo, finely crystalline tan scattered vuggy pore & hairline fractures & dead oil stain, 4752 $\frac{1}{2}$ -4754 $\frac{1}{2}$, dolo, finely crystalline tan w/shaley streaks, 4754 $\frac{1}{2}$ -4755, dolo, finely crystalline tan, 5% scattered vuggy pore w/dead oil stain, 4755-4759 $\frac{1}{2}$, dolo, finely crystalline tan, no shows, 4759 $\frac{1}{2}$ -4760, dolo, finely crystalline tan 5% pin point pore, inner crystals, pore, good stain & fluor, bleeding oil, 4760-4762, dolo, finely crystalline tan, no shows, 4762-4765, dolo, finely crystalline tan 5% pinpoint & inner crystals pore, good stain & fluorescence, bleeding oil, 4765-4770, dolo, finely crystalline tan w/black shale streaks, no shown.

ACIDIZING OR OTHER COMPLETION OPERATIONS

- 6-6-55 Western attempted to Control-frac perfs 4692-4701 & 4707-4715 w/4000 gals Jel oil + 4000# sand, TP: 5400-10300-9800, CP: 2500 after 3000 gals frac in, tubing pressure went to 10300, started oil flush, got 17 bbls in tubing, packer came up hole 8', casing pressure did not increase, shut down treatment, time 1 hr 10 min, rate 5 $\frac{1}{2}$ BPM to $\frac{1}{2}$ BPM, shut in 4 hrs, CP: 2500, TP: 1200.
- 6-8-55 Western acidized perfs 4692-4701 & 4707-4715 w/3000 gals 15% XRSLSST, TP: 4000-3200-3500, CP: 1100-2900, packer leaking, time 45 min, inj. rate 2 $\frac{1}{2}$ BPM.
- 6-12-55 Western reacidized perfs. 4692-4701 & 4707-4715 w/10000 gals 15% SLT W/XR-1, time 50 min., inj. rate 4.8 BPM, TP: 5000-4200-4300, CP: 2000-3000-3200.