

N.

(Revised 7/1/83)
(Form C-105)

AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE OCC

1955 AUG 19 PM 1:09
WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE.

Magnolia Petroleum Company

(Company or Operator)

State Bridges

(Lease)

Well No. 75, in NW $\frac{1}{4}$ of SE $\frac{1}{4}$, of Sec. 11, T. 17N, R. 34E, NMPM.Vacuum Pool, Lea County.Well is 1980 feet from East line and 1980 feet from South lineof Section 11. If State Land the Oil and Gas Lease No. is B-1520.Drilling Commenced June 19, 1955. Drilling was Completed July 17, 1955.Name of Drilling Contractor D & D Drilling CompanyAddress 1412 Magnolia Building, Dallas, TexasElevation above sea level at Top of Tubing Head 4053. The information given is to be kept confidential until

, 19.

OIL SANDS OR ZONES

No. 1, from 4650 to 4760 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8 5/8	24	New	1558	Howoo			Surface String
5 1/2	14	New	4760	Howoo		4684-4710	Oil String

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
12 1/4	8 5/8	1558	750	Pump & Plug		
7 7/8	5 1/2	4760	1350	Pump & Plug		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

(See Attached Sheet)

Result of Production Stimulation

Depth Cleaned Out

RI D OF DRILL-STEM AND SPECIAL TEST

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 4760 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing July 29, 1955

OIL WELL: The production during the first 24 hours was 70.5 barrels of liquid of which 96.4% was oil; 0% was emulsion; 3.6% water; and 0% was sediment. A.P.I. Gravity 34.2° @ 60°

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy.	1645	T. Devonian	T. Ojo Alamo
T. Salt	1755	T. Silurian	T. Kirtland-Fruitland
B. Salt	2727	T. Montoya	T. Farmington
T. Yates	2918	T. Simpson	T. Pictured Cliffs
T. Brown Line	3135	T. McKee	T. Menefee
T. Queen	3875	T. Ellenburger	T. Point Lookout
T. Grayburg		T. Gr. Wash	T. Mancos
T. San Andres	4660	T. Granite	T. Dakota
T. Glorieta		T.	T. Morrison
T. Drinkard		T.	T. Penn.
T. Tubbs		T.	T.
T. Abo		T.	T.
T. Penn		T.	T.
T. Miss		T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1428	1428	Caliche, Red Bed & Gyp				
1428	3115	1687	Anhydrite, Red Bed & Salt				
3115	3482	367	Anhydrite & Gyp				
3482	3697	215	Anhydrite & Lime				
3697	3849	152	Anhydrite & Gyp				
3849	4372	523	Anhydrite & Lime				
4372	4609	237	Lime				
4609	4650	41	Lime & Sand				
4650	4670	20	Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

August 16, 1955 (Date)

Company or Operator Anadolia Petroleum Company Address Box 727, Kermitt, Texas
Name E. H. Blundell Position or Title District Superintendent