NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES HOBBS OFFICE 000

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified into bein. Scopy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

Notice of Intention	Notice of Intention to		Notice of Intention		
TO CHANGE PLANS	TEMPORARILY ABANDON WEL	L	TO DRILL DEEPER		
NOTICE OF INTENTION TO PLUG WELL	NOTICE OF INTENTION TO PLUG BACK		Notice of Intention to Set Liner		
Notice of Intention to Squeeze	NOTICE OF INTENTION TO ACIDIZE		Notice of Intention to Shoot (Nitro)		
NOTICE OF INTENTION TO GUN PERFORATE	NOTICE OF INTENTION (OTHER) Sand Frac	x	Notice of Intention (Other)		
OIL CONSERVATION COMMI	TEXACO Inc., P. O. I	Box 352			
SANTA FE, NEW MEXICO	Midland, Texas		September	30. 1959	
· · · · · · · · · ·	(Place)	(Place)		(Date)	
Gentlemen:					
Following is a Notice of Inter	ation to do certain work as described below	w at the		•••••••••••••••••••••••••••••••••••••••	
	State N.M. WW or Operator) 13 13 17-S 34-E NM				
SW 14 SE 14 of Sec	13 17-S 34-E	830 X-17D1/	Vacuum	(Unit)	
(40-acre Subdivision)		····· ·····, · • / • / • / • / • / • / • / • / • / • 	k,,	PCO	
	FULL DETAILS OF PROPOSI	ED PLAN (OF WORK		
(1	FOLLOW INSTRUCTIONS IN THE F	RULES AND	REGULATIONS)		

To increase production we propose to do the following work:

- 1. Pump well down and inject a mixture of 55 gallons of Cheplex in 500 gallons of 5 percent hydrochloric acid into the tubing-casing anulus.
- 2. After 24 hours, pull rods and tubing.

MAN

- 3. Plug back open hale from 4680' to 4650' (30') with hydromite as insurance against fracturing into water.
- 4. Fracture open hole from 1348' to 4650' with 30,000 gallons of refined oil carrying one pound per gallon of sand in 10,000 gallon stages with 1000 pounds flaked nephthalene between stages down 3-inch tubing with packer set at approximately 1300'.
- 5. Recover load oil, test, return well to production.

Approved	TEXACO Inc.
Approved OIL CONSERVATION COMMISSION	ByPosition Assistant District Superintendent Send Communications regarding well to:
By for the state of the state o	Name J. G. Blevins, Jr.
Title	Addreu P. O. Box 352 , Midland, Texas