

NEW MEXICO OIL CONSERVATION COMMISSION

Santa, Fe, New Mexico

MISCELLANEOUS NOT

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent by the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications con-sidered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO SHUT-OFF) TEST CASING	NOTICE O CHEM	F INTENTION TO SHOOT ICALLY TREAT WELL	OR
NOTICE OF INTENTION TO) CHANGE PLANS	NOTICE O	F INTENTION TO PULL (RWISE ALTER CASING	OR
NOTICE OF INTENTION TO	REPAIR WELL			
NOTICE OF INTENTION TO) DEEPEN WELL	NOTICE C	F INTENTION TO PLUG	WELL
	Midland, Texas	3J	uly 9th, 1940	
OIL CONSERVATION COMM Santa Fe, New Mexico. Gentlemen:	IISSION,	Place		Date
Following is a notice of intent	ion to do certain work a	as described below	at the	
Texas Company's Ste Company or Operator				
▶f Sec. <u>13</u> , T. <u>17</u>		, N. M. P. M.,	Vacuum	Field,
	ULL DETAILS OF 1	א זם הפגרה הם א	N OF WORK	
			TIONS OF THE COMMISS	ION
	. D 1700' -			
		-		•• • •
Set and c at 1687' with 200 casing and circula	emented 1672' sacks cement of	(81 jts) 8-	5/8" OD 28# Lapwe Ran 140' of 1" tu . Completed cemen	bing behind
Set and c at 1687' with 200 casing and circula A. M. 7-8-40.	emented 1672' sacks cement o ited with 100 s	(81 jts) 8- on bottom. sacks cement	Ran 140' of l" tu . Completed cemen	bing behind ting at 11:
Set and c at 1687' with 200 casing and circula A. M. 7-8-40.	emented 1672' sacks cement o ted with 100 s	(81 jts) 8- on bottom. sacks cement	Ran 140' of 1" tu	bing behind ting at 11:
Set and c at 1687' with 200 casing and circula A. M. 7-8-40. Anticipat	emented 1672' sacks cement o ted with 100 s	(81 jts) 8- on bottom. sacks cement	Ran 140' of l" tu . Completed cemen	bing behind ting at 11:
Set and c at 1687' with 200 casing and circula A. M. 7-8-40. Anticipat	emented 1672' sacks cement o ted with 100 s	(81 jts) 8- on bottom. sacks cement	Ran 140' of l" tu . Completed cemen	bing behind ting at 11:
Set and c at 1687' with 200 casing and circula A. M. 7-8-40. Anticipat	emented 1672' sacks cement o ted with 100 s	(81 jts) 8- on bottom. sacks cement	Ran 140' of l" tu . Completed cemen	bing behind ting at 11:
Set and c at 1687' with 200 casing and circula A. M. 7-8-40. Anticipat	emented 1672' sacks cement o ted with 100 s	(81 jts) 8- on bottom. sacks cement	Ran 140' of l" tu . Completed cemen	bing behind ting at 11:
Set and o at 1687' with 200 casing and circula A. M. 7-8-40. Anticipat pressure method af	emented 1672' sacks cement o ted with 100 s	(81 jts) 8- on bottom. sacks cement	Ran 140' of l" tu . Completed cemen	bing behind ting at 11:
Set and c at 1687' with 200 casing and circula A. M. 7-8-40. Anticipat pressure method af	emented 1672' sacks cement of ited with 100 s e drilling plu 'ter 60 hours.	(81 jts) 8- on bottom. sacks cement ng and testi	Ran 140' of l" tu . Completed cemen	bing behind ting at 11:
Set and o at 1687' with 200 casing and circula A. M. 7-8-40. Anticipat pressure method af	emented 1672' sacks cement of ited with 100 s e drilling plu 'ter 60 hours.	(81 jts) 8- on bottom. sacks cement ng and testi	Ran 140' of 1" tu . Completed cemen	bing behind ting at 11:
Set and c at 1687' with 200 casing and circula A. M. 7-8-40. Anticipat pressure method af	emented 1672' sacks cement of ited with 100 s e drilling plu 'ter 60 hours.	(81 jts) 8- on bottom. sacks cement ag and testi the THE TE By Position D	Ran 140' of 1" tu Completed cemen ag casing shut-of Company of Operator Company of Operator	bing behind ting at 11: f by nåent
Set and c at 1687' with 200 casing and circula A. M. 7-8-40. Anticipat pressure method af	emented 1672' sacks cement of ited with 100 s e drilling plu 'ter 60 hours.	(81 jts) 8- on bottom. sacks cement ag and testi the THE TE By Position D	Ran 140' of 1" tu . Completed cemen	bing behind ting at 11: f by nåent
Set and c at 1687' with 200 casing and circula A. M. 7-8-40. Anticipat pressure method af	emented 1672' sacks cement of ited with 100 s of drilling plu ter 60 hours.	(81 jts) 8- on bottom. sacks cement ag and testi THE TE By Position _D Send	Ran 140' of 1" tu Completed cemen ag casing shut-of Company of Operator Company of Operator	bing behind ting at 11: f by <u>naent</u>

PDG, Jr-JSD

Title