

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

The Texas Company

Box 1720, Fort Worth, Texas

St. of N.M. "AC"

Well No. 2

In NW 1/4 SE 1/4

of Sec. 2

T. 18-S

R. 34-E

N. M. P. M.

Vacuum

Field,

Lea

County.

Well is 660 feet south of the North line and 1980 feet west of the East line of SE 1/4 of Sec. 2

If State land the oil and gas lease is No. B-1189 Assignment No.

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is The Texas Company Address Box 2332, Houston, Texas

Drilling commenced 10-28 1940 Drilling was completed 11-26 1940

Name of drilling contractor American Drlg. Corp Address Box 1665, Hobbs, N. M.

Elevation above sea level at top of casing 4017 feet at derrick floor.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 4510 to 4710 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
8-5/8	32#	10-V	LW	1643	Baker	Guide			
5-1/2	15#	8-R	Elec. Weld	4213	"	"			
2" EUE	4.7#	8-R	Smls.	4658'	None				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	8-5/8	1644	265	Halliburton		
	5-1/2	4206	200	"		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment Neither shot nor acidized

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 4710 feet, and from feet to feet

Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing 11-26 1940

The production of the first 6 hours was 136 barrels of fluid of which 100 % was oil; %

emulsion; % water; and % sediment. Gravity, Box API - 38

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in. G. O. R. 457

EMPLOYEES

H. E. Kennitz Driller J. R. Branscum Driller

H. G. Mills Driller Otis Moore Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 16

Midland, Texas, 12-16-40

day of December 19 40

Name

Position District Superintendent

Representing THE TEXAS COMPANY

My Commission expires 6-1-41

Address Box 1270, Midland, Texas