

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-02276
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Vacuum Grayburg San Andres Unit
8. Well No. 21
9. Pool name or Wildcat Vacuum Grayburg San Andres

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator
Texaco Producing Inc.

3. Address of Operator
P.O. Box 730 Hobbs nm

4. Well Location
Unit Letter L : 1980 Feet From The South Line and 660 Feet From The west Line

Section 2 Township 18S Range 34E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
4027 DF

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 6-25-90 thru 7-12-90

1. MURV P.U., TOH w/prod equip, TIH w/bulldog bailer c/o to 4655 - TOH
2. TIH w/ 4.75 Kut Rite Shoe - WP jars - 6 DC on 2.875 tbg
3. Attempt to circulate - leak in csg TOH w/shoe - TIH w/RBP set @ 4055
4. Locate csg leak @ 874 - 937 - 4 BPM @ 250 psi circ to subface - spot sand on RBP - DH
5. Pump 339 sxs c/c w/ 2% CACL - Circ to surface
6. TIH w/bit & DC - tbg cmt @ 660' - Drill cmt to 920' - Test csg to 300 psi - ok - TOH w/bit
7. TIH w/ret head - wash sand - latch on - TOH w/RPB
8. TIH w/ Impression block - TOH - TIH w/ skirted taper tap - on latch TOH - TIH w/Clu low socket no catch - TOH - STIH w/oper shot - no latch - TOH
9. TIH w/TRTG pkr set @4077
10. Acidize OH 4232 - 4700 w/1000 gal 15% NEFE & Scl sqz w/ 4 drums GYptron T-133
Max 1000, Min 0, AIR 3.5 BPM, ISIP 650, 15 min 540
11. TOH w/pkr - TIH w/prod equip return to rpod.
Prior 24 BO 369 BW After 22 BO 415 BW

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Richard DeSoto TITLE Engineering Technician DATE 7-28-90

TYPE OR PRINT NAME Richard DeSoto

TELEPHONE NO.

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: