

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
B-3936	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name	
2. Name of Operator		8. Farm or Lease Name	
Texaco Inc.		West Vacuum Unit	
3. Address of Operator		9. Well No.	
P. O. Box 728, Hobbs, New Mexico 88240		41	
4. Location of Well		10. Field and Pool, or Wildcat	
UNIT LETTER B 330 FEET FROM THE North LINE AND 1650 FEET FROM		Vacuum Grayburg	
THE East LINE, SECTION 4 TOWNSHIP 18-S RANGE 34-E NMPM.		San Andres	
15. Elevation (Show whether DF, RT, GR, etc.)		12. County	
4048' (DF)		Lea	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	
		OTHER Repair Water Flow <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Rigged up. Pull rods & pump. Install BOP. Pull tubing.
2. Set RBP @ 3998' & dump 20' Sand on plug. Perforate 5 1/2" Csg w/2-JS @ 1643'.
3. Set cement retainer @ 1550'. Cement perfs. @ 1643' w/300 Sx. Class 'H' Cement containing 2% CaCl. Cement circulated. Squeeze w/add'l 200 Sx. Class 'H' Cement. WOC. DOC. Tested OK.
4. Install pumping equipment. Test & return to production.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Asst. Dist. Mgr. DATE 6-4-81

APPROVED BY [Signature] TITLE  DATE JUN 14 1981

CONDITIONS OF APPROVAL, IF ANY: