

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE OCC

## MISCELLANEOUS NOTICES

1960 JAN 18 AM 7:54

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<b>X</b>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICOHobbs, New Mexico  
(Place)January 15, 1960  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

**Sunray Mid-Continent Oil Company** **N.M. State "G"** Well No. **3** in **K**  
(Company or Operator) (Unit)  
**NE**  $\frac{1}{4}$  **SW**  $\frac{1}{4}$  of Sec. **7**, T. **18S**, R. **34E**, NMPM., ..... Pool  
(40-acre Subdivision)  
**Lea** County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

We propose to P&amp;A this well as follows:

1. cut off 5 1/2" casing at approx 3000' and pull same
2. Place 25 sz plug across cut-off point at approx 3000'
3. Place 25 sz plug at 1800'
4. Place 10 sz plug at top of surface casing *25 sz plug in + cut off surface*
5. Install 4"x4" permanent well marker
6. Offset leases have been notified as per attached letter
7. Well Status: Surf esg 13 3/8" @ 240', cnt circ. TD 5443'. Mud 5443-4689'. 5 1/2" esg @ 4689'. Original top of cnt 3470'. Top of cnt plug inside 5 1/2" esg @ 4630'. Queen perfs 4597-4622'. Cast iron bridge plug @ 4410' w/1 sz cnt on top. Squeeze perfs 3450', squeezed w/126 sz 1-1, Stratocrete 4 1/2 gal, top cnt 3052'. Yates perfs 3324-38'. Well has never produced oil.

Approved....., 19.....  
Except as follows:

**Sunray Mid-Continent Oil Company**  
Company or Operator

By.....

R. E. Statton

Position.....

District Engineer

Send Communications regarding well to:

Approved  
OIL CONSERVATION COMMISSION

By.....

Name. C. T. McClanahan

Title.....

Address. Box 128, Hobbs, New Mexico