NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

Notice of Intention		Notice of Intention to	NOTICE OF INTENTION
to Change Plans		Temporarily Abandon Well	TO DRILL DEEPER
NOTICE OF INTENTION	X	Notice of Intention	Notice of Intention
TO PLUG WELL		to Plug Back	to Set Liner
Notice of Intention		Notice of Intention	Notice of Intention
to Squeeze		to Acidize	to Shoot (Nitro)
Notice of Intention		Notice of Intention	Notice of Intention
to Gun Perforate		(Other)	(Other)

OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO

Odessa, Texas

September 26, 1962

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.

Forest Oll Corporation

Forest Oll Corporation

Intended to the set of t

(40-acre Subdivision)

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

This well was drilled to a total depth of 9,198' into the Bone Springs Formation. 13-3/8" O.D. casing was set at 364.28, comented with 325 sacks coment. Coment circulated. 8-5/8" OD casing was set at 4,971', comented with 700 sacks 50/50 Posmix-incor coment, 100 sacks Nest. Top coment at 2990'. No productive formations were found in this well.

On 9-24-62 verbal permission was given by Mr. G. F. Engbrecht to plug and abandon this well as follows: 35 sacks cement from 8898-8762', 25 sacks 8510-8413'; 25 sacks 6700-6603', 35 sacks 5020-4923', and a Baker Model "N" C.I. bridge plug set in 8-5/8" OD casing at 3500'. An attempt will be made to recover a possible 2900' of 8-5/8" OD casing after which a 35 sack plug will be spotted at point of separation, and 35 sacks at bottom of 13-3/8" OD casing with 10 sacks in the top. A steel plate will be welded on top of 13-3/8" OD casing and a 4" steel marker installed on top of the sealed casing.

	Forest Oli Corporation	
Approved	By	
	Pauline Division Production Superintendent	
Approved	Send Communications regarding well to:	
OIL CONSERVATION COMMISSION	J. R. Wright, Forest Oli Corporation	
5y	P. O. Box 4105, Odessa, Texas	
Tille	Address	